

### Overview

## HPE Aruba Networking 2930F Switch Series

The HPE Aruba Networking 2930F Switch Series is designed for customers creating smart digital workplaces that are optimized for mobile users with an integrated wired and wireless approach. These convenient Layer 3 network switches include built-in uplinks and PoE power and are simple to deploy and manage with advanced security and network management tools like HPE Aruba Networking ClearPass Policy Manager, HPE Aruba Networking Management Software (AirWave) and cloud-based HPE Aruba Networking Central.

A powerful HPE Aruba Networking ProVision ASIC delivers performance, robust feature support and value with programmability for the latest applications. Stacking with Virtual Switching Framework (VSF) provides simplicity and scalability. The 2930F supports built-in 1GbE or 10GbE uplinks, PoE+, Access OSPF routing, Dynamic Segmentation, robust QoS, RIP routing, and IPv6 with no software licensing required.

The HPE Aruba Networking 2930F Switch Series provides a convenient and cost-effective access switch solution that can be quickly set up with Zero Touch Provisioning. The robust basic Layer 3 feature set includes a limited lifetime warranty.



**HPE Aruba Networking 2930F Switch Series**

### Key Features

- HPE Aruba Networking Layer 3 switch series with VSF stacking, static, RIP and Access OSPF Routing, dynamic segmentation, ACLs, and robust QoS
- Supports cloud and on-premises management. And advanced policy management using HPE Aruba Networking ClearPass
- Convenient built-in 1GbE or 10GbE uplinks and up to 740 W PoE+
- Software-defined ready with REST APIs and OpenFlow support
- Simple deployment with Zero Touch Provisioning

### Standard Features

#### Enhanced Capabilities

##### Unified Wired and Wireless Support

- **Supports unified wired and wireless policies**

HPE Aruba Networking ClearPass Policy Manager

- **Switch auto-configuration**

automatically configures switch for different settings such as VLAN, CoS, PoE max power, and PoE priority when an HPE Aruba Networking access point is detected.

- **User role**

defines a set of switch-based policies in areas such as security, authentication, and QoS. A user role can be assigned to a group of users or devices, using switch-based local user role or download from ClearPass.

- **Dynamic segmentation**

automatically enforces user, device, and application-aware policies on HPE Aruba Networking wired and wireless networks. Automated device profiling, role-based access control, and Layer 7 firewall features deliver enhanced visibility and performance for a better overall experience for both IT and end users alike.

provides a secured tunnel to transport network traffic on a per-port or per-user-role basis to an HPE Aruba Networking controller. In per-user-role Tunneled Node, users are authenticated with ClearPass Policy Manager which can direct the traffic to be tunneled to an HPE Aruba Networking controller or switch locally.

- **Static IP visibility**

allows ClearPass to do accounting for clients with static IP address

### Software-defined networks

- **REST APIs and OpenFlow**

Supports multiple programmatic interfaces, including REST APIs and Openflow 1.0 and 1.3, to enable automation of network operations, monitoring, and troubleshooting.

### Quality of Service (QoS)

- **Traffic prioritization (IEEE 802.1p)**

for classification into eight priority levels mapped to eight queues

- **Layer 4 prioritization**

based on TCP/UDP port numbers

- **Class of Service (CoS)**

sets the IEEE 802.1p priority tag based on IP address, IP Type of Service (ToS), Layer 3 protocol, TCP/UDP port number, source port, and DiffServ

- **Rate limiting**

sets per-port ingress enforced maximums and per-port, per-queue minimums

- **Large buffers**

provide graceful congestion management

- **Unknown Unicast Rate Limiting**

throttles unicast packets with unknown destination addresses and limits flooding on the VLAN

### Connectivity

- **Convenient built-in 10 Gbps Ethernet (4 x SFP+) uplinks**

available on select models

- **Auto-MDIX**

### Standard Features

- provides automatic adjustments for straight-through or crossover cables on all 10/100 and 10/100/1000 ports
- 12-port fanless model available**  
12x 1Gbps Ethernet PoE+ ports and four built-in uplinks (2x SFP+ and 2x 1GBASE-T). Built-in power supply.
- IEEE 802.3at Power over Ethernet (PoE+)**  
provides up to 30 W per port that allows support of the latest PoE+-capable devices such as IP phones, wireless access points, and security cameras, as well as any IEEE 802.3af-compliant end device; eliminates the cost of additional electrical cabling and circuits that would otherwise be necessary in IP phone and WLAN deployments
- Support for pre-standard PoE** detects and provides power to pre-standard PoE devices

### IPv6

- IPv6 host**  
enables switches to be managed in an IPv6 network
- Dual stack (IPv4 and IPv6)**  
transitions from IPv4 to IPv6, supporting connectivity for both protocols
- MLD snooping**  
forwards IPv6 multicast traffic to the appropriate interface
- IPv6 ACL/QoS**  
supports ACL and QoS for IPv6 network traffic
- IPv6 routing**  
supports static and RIPng protocols
- Security**  
provides RA guard, DHCPv6 protection, dynamic IPv6 lockdown, and ND snooping

### Performance and efficiency

- Energy-efficient design**
  - 80 PLUS Silver Certified power supply**  
increases power efficiency and savings
  - Energy-efficient Ethernet (EEE) support**  
reduces power consumption in accordance with IEEE 802.3az
- Designed with the latest HPE Aruba Networking ProVision ASIC**  
providing very low latency, increased packet buffering, and adaptive power consumption
- Selectable queue configurations**  
allows for increased performance by selecting the number of queues and associated memory buffering that best meet the requirements of the network applications
- Stacking topology**
  - Virtual Switching Framework (VSF) front plane stacking creates one virtual resilient switch from up to eight switches.  
**Notes:** Requires HPE Aruba Networking OS-Switch 16.06 software.
  - Ring topology supports up to an 8-member stack
  - Virtualized switching provides simplified management as the switches act as a single chassis when stacked

### Convergence

- IP multicast snooping and data-driven IGMP**  
automatically prevent flooding of IP multicast traffic
- LLDP-MED (Media Endpoint Discovery)**

### Standard Features

- defines a standard extension of LLDP that stores values for parameters such as QoS and VLAN to configure automatically network devices such as IP phones
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP)**  
facilitates easy mapping using network management applications with LLDP automated device discovery protocol
- **PoE and PoE+ allocations**  
support multiple methods (automatic, IEEE 802.3at dynamic, LLDP-MED fine grain, IEEE 802.3af device class, or user-specified) to allocate and manage PoE/PoE+ power for more efficient energy savings
- **Local MAC Authentication**  
assigns attributes such as VLAN and QoS using a locally configured profile that can be a list of MAC prefixes
- **IP multicast routing**  
includes PIM Sparse and Dense modes to route IP multicast traffic (limited to 16 interfaces)
- **Protocol Independent Multicast for IPv6**  
supports one-to-many and many-to-many media casting use cases such as IPTV over IPv6 networks

### Monitor and diagnostics

- **Digital optical monitoring of SFP+ and 1000BASE-T transceivers**  
allows detailed monitoring of the transceiver settings and parameters

### Resiliency and high availability

- **IEEE 802.1s Multiple Spanning Tree**  
provides high link availability by allowing multiple spanning trees; provides legacy support for IEEE 802.1d and IEEE 802.1w
- **Virtual Router Redundancy Protocol (VRRP)**  
allows groups of two routers to dynamically back each other up to create highly available routed environments for IPv4 and IPv6 networks (limited to 128 VRs)
- **IEEE 802.3ad link-aggregation-control protocol (LACP) and port trunking**  
support up to 60 static or dynamic trunks with each trunk having up to eight links (ports) per static trunk
- **SmartLink**  
provides easy-to-configure link redundancy of active and standby links
- **SNMPv1, v2, and v3**  
provide complete support of SNMP; provide full support of industry-standard Management Information Base (MIB) plus private extensions; SNMPv3 supports increased security using encryption

### Simplified configuration and management

- **HPE Aruba Networking Central support**  
cloud based management platform offers simple, secure, and cost effective way to manage switches
- **Zero-Touch Provisioning (ZTP)**  
simplifies installation of the switch infrastructure using HPE Aruba Networking Activate or a DHCP-based process with AirWave and Central Network Management
- **Built-in programmable and easy-to-use REST API interface**  
provides configuration automation for campus networks
- **Flexible management with same hardware**  
supports both cloud-based Central and on-premises AirWave with the same hardware, ensuring management platform changes without ripping and replacing switching infrastructure

### Standard Features

---

#### Manageability

- **Dual flash images**  
provides independent primary and secondary operating system files for backup while upgrading
- **Friendly port names**  
allow assignment of descriptive names to ports
- **Find-Fix-Inform feature**  
finds and fixes common network problems automatically, then informs administrator
- **Supports multiple configuration files**  
stored to a flash image
- **RMON, XRMON, and sFlow**  
provide advanced monitoring and reporting capabilities for statistics, history, alarms, and events
- **Troubleshooting**  
ingress and egress port monitoring enable more efficient network problem solving
- **Unidirectional link detection (UDLD)**  
monitors the link between two switches and blocks the ports on both ends of the link if the link goes down at any point between the two devices
- **IP service level agreements (SLA) for voice**  
monitor quality of voice traffic using the UDP jitter and UDP jitter for VoIP tests

---

#### Software releases

- to find software for your product, refer to <http://www.hpe.com/networking/support>;

---

#### Layer 3 services

- **DHCP server**  
centralizes and reduces the cost of IPv4 address management

---

#### Layer 2 switching

- **IEEE 802.1ad Q-in-Q**  
increases the scalability of an Ethernet network by providing a hierarchical structure; connects multiple LANs on a high-speed campus or metro network
- **VLAN Support and Tagging**  
supports IEEE 802.1Q (4094 VLAN IDs) and 2K VLANs simultaneously
- **Jumbo packet support**  
improves the performance of large data transfers; supports frame size of up to 9220 bytes
- **IEEE 802.1v protocol VLANs**  
isolate select non-IPv4 protocols automatically into their own VLANs
- **Rapid Per-VLAN Spanning Tree (RPVST+)**  
allows each VLAN to build a separate spanning tree to improve link bandwidth usage; is compatible with PVST+
- **GVRP and MVRP**  
allows automatic learning and dynamic assignment of VLANs
- **VxLAN**  
encapsulation (tunneling) protocol for overlay network that enables a more scalable virtual network deployment

---

### Standard Features

#### Layer 3 routing

- **Static IP routing**  
provides manually configured routing; includes ECMP capability
- **256 static and 10,000 RIP routes**  
facilitate segregation of user data, without adding external hardware
- **Routing Information Protocol (RIP)**  
provides RIPv1, RIPv2, and RIPng routing
- **Access OSPF**  
provides OSPFv2 and OSPFv3 protocols for routing between access and the next layer on the LAN.  
Only one OSPF area and up to 8 interfaces are supported
- **Policy-based routing**  
uses a classifier to select traffic that can be forwarded based on policy set by the network administrator (limited to 16 next-hop routes)

#### Customer first, customer last support

When your network is important to your business, then your business needs the backing of HPE Aruba Networking Support Services. Partner with HPE Aruba Networking product experts to increase your team productivity, keep pace with technology advances, software releases, and obtain break-fix support.

- Foundation Care for HPE Aruba Networking support services include priority access to HPE Aruba Networking Technical Assistance Center (TAC) engineers 24x7x365, flexible hardware and onsite support options, and total coverage for HPE Aruba Networking products. HPE Aruba Networking switches with assigned HPE Aruba Networking Central subscriptions benefit with option for additional hardware support only.
- HPE Aruba Networking Pro Care adds fast access to senior HPE Aruba Networking TAC engineers, who are assigned as a single point of contact for case management, reducing the time spent addressing and resolving issues.

For complete details on Foundation Care and HPE Aruba Networking Pro Care, please visit:

<https://www.hpe.com/us/en/networking/hpe-aruba-networking-support-services.html>

#### Warranty and support

- **Limited Lifetime Warranty**

see <https://www.hpe.com/us/en/networking/hpe-aruba-networking-support-services.html> for warranty and support information included with your product purchase.

#### Security

- **Control Plane Policing set rate limit on control protocols to protect CPU overload from DOS attacks**
- **Multiple user authentication methods**
  - uses an IEEE 802.1X supplicant on the client in conjunction with a RADIUS server to authenticate in accordance with industry standards
  - supports Web-based authentication
  - supports MAC-based authentication
- **Authentication flexibility**
  - **Multiple IEEE 802.1X users per port**  
provides authentication of multiple devices on a single port; prevents a user from "piggybacking" on another user's IEEE 802.1X authentication
  - **Concurrent IEEE 802.1X, Web, and MAC authentication schemes per port**  
switch port will accept up to 32 sessions of IEEE 802.1X, Web, and MAC authentications
- **TPM-based Security**

### Standard Features

includes a Trusted Platform Module (TPM) for secure hardware-based generation and storage of cryptographic keys that can be used for a variety of authentication purposes

- **Access control lists (ACLs)**  
provide IP Layer 3 filtering based on source/destination IP address/subnet and source/destination TCP/UDP port number
- **Source-port filtering**  
allows only specified ports to communicate with each other
- **RADIUS/TACACS+**  
eases switch management security administration by using a password authentication server
- **Secure shell**  
encrypts all transmitted data for secure remote CLI access over IP networks
- **Secure Sockets Layer (SSL)**  
encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch
- **Port security**  
allows access only to specified MAC addresses, which can be learned or specified by the administrator
- **Radius over TLS (RadSec)**  
allows users to use a more secure and reliable mode of communications between switch and radius servers over unsecure networks
- **MAC address lockout**  
prevents particular configured MAC addresses from connecting to the network
- **Secure FTP**  
allows secure file transfer to and from the switch; protects against unwanted file downloads or unauthorized copying of a switch configuration file
- **Switch management logon security**  
helps secure switch CLI logon by optionally requiring either RADIUS or TACACS+ authentication
- **Custom banner**  
displays security policy when users log in to the switch
- **STP BPDU port protection**  
blocks Bridge Protocol Data Units (BPDUs) on ports that do not require BPDUs, preventing forged BPDU attacks
- **DHCP protection**  
blocks DHCP packets from unauthorized DHCP servers, preventing denial-of-service attacks
- **Dynamic ARP protection**  
blocks ARP broadcasts from unauthorized hosts, preventing eavesdropping or theft of network data
- **STP root guard**  
protects the root bridge from malicious attacks or configuration mistakes
- **Identity-driven ACL**  
enables implementation of a highly granular and flexible access security policy and VLAN assignment specific to each authenticated network user
- **Per-port broadcast throttling**  
Configures broadcast control selectively on heavy traffic port uplinks
- **Private VLAN**  
provides network security by restricting peer-to-peer communication to prevent a variety of malicious attacks; typically a switch port can only communicate with other ports in the same community and/or an uplink port, regardless of VLAN ID or destination MAC address
- **Open authentication role**  
simplifies first-time deployment of AAA in brownfield deployments by allowing full network access for failed clients and provides instant connectivity as soon as a client is plugged-in

### Standard Features

- **Critical authentication role**  
ensures that important infrastructure devices such as IP phones are allowed network access even in the absence of a RADIUS server
- **MAC pinning**  
allows non-chatty legacy devices to stay authenticated by pinning client MAC addresses to the port until the clients logoff or get disconnected
- **Enrollment over Secure Transport (EST)**  
enhances the switch PKI infrastructure with a simpler, scalable and more secure method of certificate provisioning, re-enrollment and renewal

---

### Configuration Information

#### BTO Models

| Rule #     | Description   | SKU        |
|------------|---|------------|
| 1, 2, 3,10 | HPE Aruba Networking 2930F 12G PoE+ 2G/2SFP+ Switch <ul style="list-style-type: none"><li>• 12 RJ-45 PoE+ autosensing 10/100/1000 ports</li><li>• 2 SFP/SFP+ 1G/10G ports</li><li>• min=0 \ max=2 SFP/SFP+ Transceivers</li><li>• 1U - Height</li></ul> | JL693A     |
|            | HPE Aruba Networking 2930F 12G PoE+ 2G/2SFP+ Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>  | JL693A#B2B |
|            | HPE Aruba Networking 2930F 12G PoE+ 2G/2SFP+ Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>   | JL693A#B2C |
|            | HPE Aruba Networking 2930F 12G PoE+ 2G/2SFP+ Switch 220v <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Pwr Cord(J9936A)</li></ul>  | JL693A#B2E |
|            | HPE Aruba Networking 2930F 12G PoE+ 2G/2SFP+ Switch No Loc <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>   | JL693A#AC3 |
| 1, 2, 3,10 | HPE Aruba Networking 2930F 24G 4SFP+ Switch <ul style="list-style-type: none"><li>• 24 RJ-45 autosensing 10/100/1000 ports</li><li>• 4 SFP/SFP+ 1G/10G ports</li><li>• min=0 \ max=4 SFP/SFP+ Transceivers</li><li>• 1U - Height</li></ul>              | JL253A     |
|            | HPE Aruba Networking 2930F 24G 4SFP+ Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>  | JL253A#B2B |
|            | HPE Aruba Networking 2930F 24G 4SFP+ Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>   | JL253A#B2C |
|            | HPE Aruba Networking 2930F 24G 4SFP+ Switch 220v <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li></ul>  | JL253A#B2E |
|            | HPE Aruba Networking 2930F 24G 4SFP+ Switch No Loc <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>   | JL253A#AC3 |
| 1, 2, 3,10 | HPE Aruba Networking 2930F 48G 4SFP+ Switch <ul style="list-style-type: none"><li>• 48 RJ-45 autosensing 10/100/1000 ports</li><li>• 4 SFP/SFP+ 1G/10G ports</li><li>• min=0 \ max=4 SFP/SFP+ Transceivers</li><li>• 1U - Height</li></ul>              | JL254A     |
|            | HPE Aruba Networking 2930F 24G 4SFP+ Swch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>  | JL254A#B2B |
|            | HPE Aruba Networking 2930F 24G 4SFP+ Swch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>   | JL254A#B2C |
|            | HPE Aruba Networking 2930F 24G 4SFP+ Switch 220v <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li></ul>  | JL254A#B2E |
|            | HPE Aruba Networking 2930F 48G 4SFP+ Switch No Loc <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>   | JL254A#AC3 |
| 1, 2, 3,10 | HPE Aruba Networking 2930F 24G PoE+ 4SFP+ Switch <ul style="list-style-type: none"><li>• 24 RJ-45 PoE+ autosensing 10/100/1000 ports</li><li>• 4 SFP/SFP+ 1G/10G ports</li><li>• min=0 \ max=4 SFP/SFP+ Transceivers</li><li>• 1U - Height</li></ul>    | JL255A     |

### Configuration Information

| Rule #     | Description  | SKU        |
|------------|--|------------|
|            | HPE Aruba Networking 2930F 24G PoE+ 4SFP+ Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>  | JL255A#B2B |
|            | HPE Aruba Networking 2930F 24G PoE+ 4SFP+ Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>   | JL255A#B2C |
|            | HPE Aruba Networking 2930F 24G PoE+ 4SFP+ Switch 220v <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li></ul>  | JL255A#B2E |
|            | HPE Aruba Networking 2930F 24G PoE+ 4SFP+ Switch No Loc <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>   | JL255A#AC3 |
| 1, 2, 3,10 | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ Switch <ul style="list-style-type: none"><li>• 48 RJ-45 PoE+ autosensing 10/100/1000 ports</li><li>• 4 SFP/SFP+ 1G/10G ports</li><li>• min=0 \ max=4 SFP/SFP+ Transceivers</li><li>• 1U - Height</li></ul> | JL256A     |
|            | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>  | JL256A#B2B |
|            | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>   | JL256A#B2C |
|            | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ Switch 220v <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li></ul>  | JL256A#B2E |
|            | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ Switch No Loc <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>   | JL256A#AC3 |
| 1, 2, 3,10 | HPE Aruba Networking 2930F 8G PoE+ 2SFP+ Switch <ul style="list-style-type: none"><li>• 8 RJ-45 PoE+ autosensing 10/100/1000 ports</li><li>• 2 SFP/SFP+ 1G/10G ports</li><li>• min=0 \ max=2 SFP/SFP+ Transceivers</li><li>• 1U - Height</li></ul>   | JL258A     |
|            | HPE Aruba Networking 2930F 8G PoE+ 2SFP+ Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>   | JL258A#B2B |
|            | HPE Aruba Networking 2930F 8G PoE+ 2SFP+ Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>  | JL258A#B2C |
|            | HPE Aruba Networking 2930F 8G PoE+ 2SFP+ Switch 220v <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li></ul>   | JL258A#B2E |
|            | HPE Aruba Networking 2930F 8G PoE+ 2SFP+ Switch No Loc <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>  | JL258A#AC3 |
| 1, 3,10    | HPE Aruba Networking 2930F 24G 4SFP Switch <ul style="list-style-type: none"><li>• 24 RJ-45 autosensing 10/100/1000 ports</li><li>• 4 SFP 1G ports</li><li>• min=0 \ max=4 SFP Transceivers</li><li>• 1U - Height</li></ul>                          | JL259A     |
|            | HPE Aruba Networking 2930F 24G 4SFP Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>  | JL259A#B2B |
|            | HPE Aruba Networking 2930F 24G 4SFP Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>   | JL259A#B2C |
|            | HPE Aruba Networking 2930F 24G 4SFP Switch 220v  | JL259A#B2E |

### Configuration Information

|          | <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li></ul>   |            |
|----------|---|------------|
|          | HPE Aruba Networking 2930F 24G 4SFP Switch No Loc <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>  | JL259A#AC3 |
| Rule #   | Description   | SKU        |
| 1, 3, 10 | HPE Aruba Networking 2930F 48G PoE+ 4SFP 740W Switch <ul style="list-style-type: none"><li>• 48 RJ-45 autosensing 10/100/1000 ports</li><li>• 4 SFP 1G ports</li><li>• min=0 \ max=4 SFP Transceivers</li><li>• 1U - Height</li></ul> | JL557A     |
|          | HPE Aruba Networking 2930F 48G PoE+ 4SFP 740W Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>   | JL557A#B2B |
|          | HPE Aruba Networking 2930F 48G PoE+ 4SFP 740W Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>  | JL557A#B2C |
|          | HPE Aruba Networking 2930F 48G PoE+ 4SFP 740W Switch 220v <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li></ul>   | JL557A#B2E |
|          | HPE Aruba Networking 2930F 48G PoE+ 4SFP 740W Switch No Loc <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>  | JL557A#AC3 |
| 1, 3, 10 | HPE Aruba Networking 2930F 48G 4SFP Switch <ul style="list-style-type: none"><li>• 48 RJ-45 autosensing 10/100/1000 ports</li><li>• 4 SFP 1G ports</li><li>• min=0 \ max=4 SFP Transceivers</li><li>• 1U - Height</li></ul>           | JL260A     |
|          | HPE Aruba Networking 2930F 48G 4SFP Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>   | JL260A#B2B |
|          | HPE Aruba Networking 2930F 48G 4SFP Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>  | JL260A#B2C |
|          | HPE Aruba Networking 2930F 48G 4SFP Switch 220V <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li></ul>   | JL260A#B2E |
|          | HPE Aruba Networking 2930F 48G 4SFP Switch No Loc <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>  | JL260A#AC3 |
| 1, 3, 10 | HPE Aruba Networking 2930F 24G PoE+ 4SFP Switch <ul style="list-style-type: none"><li>• 24 RJ-45 PoE+ autosensing 10/100/1000 ports</li><li>• 4 SFP 1G ports</li><li>• min=0 \ max=4 SFP Transceivers</li><li>• 1U - Height</li></ul> | JL261A     |
|          | HPE Aruba Networking 2930F 24G PoE+ 4SFP Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>  | JL261A#B2B |
|          | HPE Aruba Networking 2930F 24G PoE+ 4SFP Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>   | JL261A#B2C |
|          | HPE Aruba Networking 2930F 24G PoE+ 4SFP Switch 220v <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li></ul>  | JL261A#B2E |
|          | HPE Aruba Networking 2930F 24G PoE+ 4SFP Switch No Loc <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>   | JL261A#AC3 |
| 1, 3, 10 | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W Switch   | JL558A     |

### Configuration Information

- 48 RJ-45 PoE+ autosensing 10/100/1000 ports
- 4 SFP 1G ports
- min=0 \ max=4 SFP Transceivers
- 1U - Height

HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W Switch PDU

JL558A#B2B

- C15 PDU Jumper Cord (NA/MEX/TW/JP)

HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W Switch

JL558A#B2C

- C15 PDU Jumper Cord (ROW)

HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W Switch

JL558A#B2E

- HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)

HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W Switch

JL558A#AC3

- No Localized Power Cord Selected

1, 3, 10 HPE Aruba Networking 2930F 48G PoE+ 4SFP Switch JL262A

- 48 RJ-45 PoE+ autosensing 10/100/1000 ports
- 4 SFP 1G ports
- min=0 \ max=4 SFP Transceivers
- 1U - Height

HPE Aruba Networking 2930F 48G PoE+ 4SFP Switch

JL262A#B2B

- C15 PDU Jumper Cord (NA/MEX/TW/JP)

HPE Aruba Networking 2930F 48G PoE+ 4SFP Switch

JL262A#B2C

- C15 PDU Jumper Cord (ROW)

HPE Aruba Networking 2930F 48G PoE+ 4SFP Switch

JL262A#B2E

- HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)

HPE Aruba Networking 2930F 48G PoE+ 4SFP Switch

JL262A#AC3

- No Localized Power Cord Selected

### TAA Compliant Chassis

| Rule #               | Description  | SKU        |
|----------------------|--|------------|
| 1, 2, 3, 4, 8, 9, 10 | HPE Aruba Networking 2930F 8G PoE+ 2SFP+ TAA-compliant Switch  | JL692A     |
|                      | <ul style="list-style-type: none"><li>• 8 RJ-45 PoE+ autosensing 10/100/1000 ports</li><li>• 2 SFP/SFP+ 1G/10G ports</li><li>• min=0 \ max=2 SFP/SFP+ Transceivers</li><li>• 1U - Height</li></ul> |            |
|                      | HPE Aruba Networking 2930F 8G PoE+ 2SFP+ TAA-compliant Switch  | JL692A#B2B |
|                      | <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>   |            |
|                      | HPE Aruba Networking 2930F 8G PoE+ 2SFP+ TAA-compliant Switch  | JL692A#B2C |
|                      | <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>  |            |
|                      | HPE Aruba Networking 2930F 8G PoE+ 2SFP+ TAA-compliant Switch  | JL692A#B2E |
|                      | <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Pwr Cord(J9936A)</li></ul>  |            |
|                      | HPE Aruba Networking 2930F 8G PoE+ 2SFP+ TAA-compliant Switch  | JL692A#AC3 |
|                      | <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>   |            |
| 1, 2, 3, 4, 8, 9, 10 | HPE Aruba Networking 2930F 24G PoE+ 4SFP+ TAA-compliant Switch   | JL263A     |

### Configuration Information

- 24 RJ-45 PoE+ autosensing 10/100/1000 ports
- 4 SFP/SFP+ 1G/10G ports
- min=0 \ max=4 SFP/SFP+ Transceivers
- 1U - Height

HPE Aruba Networking 2930F 24G PoE+ 4SFP+ TAA-compliant Switch

JL263A#B2B

- C15 PDU Jumper Cord (NA/MEX/TW/JP)

HPE Aruba Networking 2930F 24G PoE+ 4SFP+ TAA-compliant Switch

JL263A#B2C

- C15 PDU Jumper Cord (ROW)

| Rule #                 | Description   | SKU        |
|------------------------|---|------------|
|                        | HPE Aruba Networking 2930F 24G PoE+ 4SFP+ TAA Switch 220v <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li></ul>   | JL263A#B2E |
|                        | HPE Aruba Networking 2930F 24G PoE+ 4SFP+ TAA Switch No Loc <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>  | JL263A#AC3 |
| 1, 2, 3, 4,<br>8, 9,10 | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch <ul style="list-style-type: none"><li>• 48 RJ-45 PoE+ autosensing 10/100/1000 ports</li><li>• 4 SFP/SFP+ 1G/10G ports</li><li>• min=0 \ max=4 SFP/SFP+ Transceivers</li><li>• 1U - Height</li></ul> | JL559A     |
|                        | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch PDU NA, JP or TW <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>   | JL559A#B2B |
|                        | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch PDU ROW <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>   | JL559A#B2C |
|                        | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch United States 220 volt <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li></ul>  | JL559A#B2E |
|                        | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>  | JL559A#AC3 |
| 1, 2, 3, 4,<br>8, 9,10 | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ TAA-compliant Switch <ul style="list-style-type: none"><li>• 48 RJ-45 PoE+ autosensing 10/100/1000 ports</li><li>• 4 SFP/SFP+ 1G/10G ports</li><li>• min=0 \ max=4 SFP/SFP+ Transceivers</li><li>• 1U - Height</li></ul>      | JL264A     |
|                        | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ TAA Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>   | JL264A#B2B |
|                        | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ TAA Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>  | JL264A#B2C |
|                        | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ TAA Switch 220v <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li></ul>   | JL264A#B2E |
|                        | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ TAA Switch No Loc <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>  | JL264A#AC3 |

### Configuration Rules

1 The following Transceivers install into this Switch:

### Configuration Information

|        |   |        |
|--------|---|--------|
|        | HPE Aruba Networking 1G SFP LC SX 500m OM2 MMF Transceiver  | J4858D |
|        | HPE Aruba Networking 1G SFP LC LX 10km SMF Transceiver  | J4859D |
|        | HPE Aruba Networking 1G SFP LC LH 70km SMF Transceiver  | J4860D |
|        | HPE Aruba Networking 1G SFP RJ45 T 100m Cat5e Transceiver   | J8177D |
|        | HPE Aruba Networking 100M SFP LC FX 2km MMF Transceiver   | J9054D |
| 2      | The following Transceivers install into this Switch:  |        |
|        | HPE Aruba Networking 10G SFP+ LC SR 300m OM3 MMF Transceiver  | J9150D |
|        | HPE Aruba Networking 10G SFP+ LC LR 10km SMF Transceiver  | J9151E |
|        | HPE Aruba Networking 10G SFP+ LC ER 40km SMF Transceiver  | J9153D |
|        | HPE Aruba Networking 10G SFP+ to SFP+ 1m Direct Attach Copper Cable   | J9281D |
|        | HPE Aruba Networking 10G SFP+ to SFP+ 3m Direct Attach Copper Cable   | J9283D |
| 3      | Localization required on orders without #B2B, #B2C or #B2E options.   |        |
| 4      | TAA Switch Chassis are available in the US, UK, Israel, Vietnam, South Korea, India, and Taiwan only.   |        |
| 8      | The following Transceivers install into this Switch:  |        |
|        | HPE Aruba Networking 1G SFP LC SX 500m MMF TAA Transceiver  | JL745A |
|        | HPE Aruba Networking 1G SFP LC LX 10km SMF TAA Transceiver  | JL746A |
|        | HPE Aruba Networking 1G SFP RJ45 T 100m Cat5e TAA Transceiver   | JL747A |
| 9      | The following Transceivers install into this Switch:  |        |
|        | HPE Aruba Networking 10G SFP+ LC SR 300m MMF TAA Transceiver  | JL748A |
|        | HPE Aruba Networking 10G SFP+ LC LR 10km SMF TAA Transceiver  | JL749A |
| 10     | Unbuildable/FAN required, generates CFGU: If order is quoted for India and contains "#B2C" Option, then Display the following:                              |        |
|        | For BTO shipments to India:   |        |
|        | Please replace <Base Model>#B2C option with <Base Model>#AC3 in the Bill of Materials and add the appropriate INDIA PDU Power Cord below via Ad-Hoc:        |        |
|        | For Factory Integration of Power Cord, please add "#0D1" to the Power Cord SKU suffix. (Ex. JL671A#0D1)   |        |
|        | HPE Networking 2.0m C13 to C14 PDU India Power Cord   | JL671A |
|        | HPE Networking 2.5m C15 to C14 PDU India Power Cord   | JL672A |
|        | HPE Networking 2.5m C19 to C20 PDU India Power Cord   | JL673A |
| Notes: | Drop down under power supply should offer the following options and results:  |        |
|        | Switch/Router/Power Supply to PDU Power Cord - #B2B in North America, Mexico, Taiwan, and Japan or #B2C ROW. (Watson Default B2B or B2C for Rack Level CTO) |        |
|        | Switch/Router/Power Supply to Wall Power Cord - Localized Option (Watson Default for BTO and Box Level CTO)   |        |
|        | #AC3 - No Power Cord  |        |

### Rack Level Integration CTO Models

| Rule #            | Description                                 | SKU    |
|-------------------|---|--------|
| 1, 2, 3, 4, 5, 10 | HPE Aruba Networking 2930F 24G 4SFP+ Switch | JL253A |

### Configuration Information

|                     |  |            |
|---------------------|--|------------|
|                     | <ul style="list-style-type: none"><li>• 24 RJ-45 autosensing 10/100/1000 ports</li><li>• 4 SFP/SFP+ 1G/10G ports</li><li>• min=0 \ max=4 SFP/SFP+ Transceivers</li><li>• 1U - Height</li></ul>   |            |
|                     | HPE Aruba Networking 2930F 24G 4SFP+ Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>   | JL253A#B2B |
|                     | HPE Aruba Networking 2930F 24G 4SFP+ Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>  | JL253A#B2C |
|                     | HPE Aruba Networking 2930F 24G 4SFP+ Switch 220v <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li></ul>   | JL253A#B2E |
|                     | HPE Aruba Networking 2930F 24G 4SFP+ Switch No Loc <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>  | JL253A#AC3 |
| 1, 2, 3, 4,<br>5,10 | HPE Aruba Networking 2930F 48G 4SFP+ Switch <ul style="list-style-type: none"><li>• 48 RJ-45 autosensing 10/100/1000 ports</li><li>• 4 SFP/SFP+ 1G/10G ports</li><li>• min=0 \ max=4 SFP/SFP+ Transceivers</li><li>• 1U - Height</li></ul>           | JL254A     |
|                     | HPE Aruba Networking 2930F 24G 4SFP+ Swch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>   | JL254A#B2B |
|                     | HPE Aruba Networking 2930F 24G 4SFP+ Swch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>  | JL254A#B2C |
|                     | HPE Aruba Networking 2930F 24G 4SFP+ Switch 220v <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li></ul>   | JL254A#B2E |
|                     | HPE Aruba Networking 2930F 48G 4SFP+ Switch No Loc <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>  | JL254A#AC3 |
| 1, 2, 3, 4,<br>5,10 | HPE Aruba Networking 2930F 24G PoE+ 4SFP+ Switch <ul style="list-style-type: none"><li>• 24 RJ-45 PoE+ autosensing 10/100/1000 ports</li><li>• 4 SFP/SFP+ 1G/10G ports</li><li>• min=0 \ max=4 SFP/SFP+ Transceivers</li><li>• 1U - Height</li></ul> | JL255A     |
|                     | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ Switch <ul style="list-style-type: none"><li>• 48 RJ-45 PoE+ autosensing 10/100/1000 ports</li><li>• 4 SFP/SFP+ 1G/10G ports</li><li>• min=0 \ max=4 SFP/SFP+ Transceivers</li><li>• 1U - Height</li></ul> | JL256A     |
| 1, 2, 3, 4,<br>5,10 | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>  | JL256A#B2B |
|                     | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>   | JL256A#B2C |
|                     | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ Switch 220v <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li></ul>  | JL256A#B2E |
|                     | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ Switch No Loc <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>   | JL256A#AC3 |

### Configuration Information

|                  |   |            |
|------------------|---|------------|
| 1, 3, 4,<br>5,10 | HPE Aruba Networking 2930F 24G 4SFP Switch  | JL259A     |
|                  | <ul style="list-style-type: none"> <li>• 24 RJ-45 autosensing 10/100/1000 ports</li> <li>• 4 SFP 1G ports</li> <li>• min=0 \ max=4 SFP Transceivers</li> <li>• 1U - Height</li> </ul> |            |
|                  | HPE Aruba Networking 2930F 24G 4SFP Switch PDU  | JL259A#B2B |
|                  | <ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li> </ul>  |            |
|                  | HPE Aruba Networking 2930F 24G 4SFP Switch PDU  | JL259A#B2C |
|                  | <ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (ROW)</li> </ul>   |            |
|                  | HPE Aruba Networking 2930F 24G 4SFP Switch 220v   | JL259A#B2E |
|                  | <ul style="list-style-type: none"> <li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li> </ul>   |            |
|                  | HPE Aruba Networking 2930F 24G 4SFP Switch No Loc   | JL259A#AC3 |
|                  | <ul style="list-style-type: none"> <li>• No Localized Power Cord Selected</li> </ul>  |            |
| 1, 3,10          | HPE Aruba Networking 2930F 48G PoE+ 4SFP 740W Switch  | JL557A     |
|                  | <ul style="list-style-type: none"> <li>• 48 RJ-45 autosensing 10/100/1000 ports</li> <li>• 4 SFP 1G ports</li> <li>• min=0 \ max=4 SFP Transceivers</li> <li>• 1U - Height</li> </ul> |            |
|                  | HPE Aruba Networking 2930F 48G PoE+ 4SFP 740W Switch PDU  | JL557A#B2B |
|                  | <ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li> </ul>  |            |
|                  | HPE Aruba Networking 2930F 48G PoE+ 4SFP 740W Switch PDU  | JL557A#B2C |
|                  | <ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (ROW)</li> </ul>   |            |
|                  | HPE Aruba Networking 2930F 48G PoE+ 4SFP 740W Switch 220v   | JL557A#B2E |
|                  | <ul style="list-style-type: none"> <li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li> </ul>   |            |
| <b>Rule #</b>    | <b>Description</b>  | <b>SKU</b> |
|                  | HPE Aruba Networking 2930F 48G PoE+ 4SFP 740W Switch No Loc   | JL557A#AC3 |
|                  | <ul style="list-style-type: none"> <li>• No Localized Power Cord Selected</li> </ul>  |            |
| 1, 3, 4,<br>5,10 | HPE Aruba Networking 2930F 48G 4SFP Switch  | JL260A     |
|                  | <ul style="list-style-type: none"> <li>• 48 RJ-45 autosensing 10/100/1000 ports</li> <li>• 4 SFP 1G ports</li> <li>• min=0 \ max=4 SFP Transceivers</li> <li>• 1U - Height</li> </ul> |            |
|                  | HPE Aruba Networking 2930F 48G 4SFP Switch PDU  | JL260A#B2B |
|                  | <ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li> </ul>  |            |
|                  | HPE Aruba Networking 2930F 48G 4SFP Switch PDU  | JL260A#B2C |
|                  | <ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (ROW)</li> </ul>   |            |
|                  | HPE Aruba Networking 2930F 48G 4SFP Switch 220V   | JL260A#B2E |
|                  | <ul style="list-style-type: none"> <li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li> </ul>   |            |
|                  | HPE Aruba Networking 2930F 48G 4SFP Switch No Loc   | JL260A#AC3 |
|                  | <ul style="list-style-type: none"> <li>• No Localized Power Cord Selected</li> </ul>  |            |
| 1, 3, 4,<br>5,10 | HPE Aruba Networking 2930F 24G PoE+ 4SFP Switch   | JL261A     |

### Configuration Information

- 24 RJ-45 PoE+ autosensing 10/100/1000 ports
- 4 SFP 1G ports
- min=0 \ max=4 SFP Transceivers
- 1U - Height

| Rule #         | Description   | SKU        |
|----------------|---|------------|
|                | HPE Aruba Networking 2930F 24G PoE+ 4SFP Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>  | JL261A#B2B |
|                | HPE Aruba Networking 2930F 24G PoE+ 4SFP Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>   | JL261A#B2C |
|                | HPE Aruba Networking 2930F 24G PoE+ 4SFP Switch 220v <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li></ul>  | JL261A#B2E |
|                | HPE Aruba Networking 2930F 24G PoE+ 4SFP Switch No Loc <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>   | JL261A#AC3 |
| 1, 3, 10       | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W Switch <ul style="list-style-type: none"><li>• 48 RJ-45 PoE+ autosensing 10/100/1000 ports</li><li>• 4 SFP 1G ports</li><li>• min=0 \ max=4 SFP Transceivers</li><li>• 1U - Height</li></ul> | JL558A     |
|                | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>  | JL558A#B2B |
|                | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>   | JL558A#B2C |
|                | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W Switch 220v <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li></ul>  | JL558A#B2E |
|                | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W Switch No Loc <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>   | JL558A#AC3 |
| 1, 3, 4, 5, 10 | HPE Aruba Networking 2930F 48G PoE+ 4SFP Switch <ul style="list-style-type: none"><li>• 48 RJ-45 PoE+ autosensing 10/100/1000 ports</li><li>• 4 SFP 1G ports</li><li>• min=0 \ max=4 SFP Transceivers</li><li>• 1U - Height</li></ul>       | JL262A     |
|                | HPE Aruba Networking 2930F 48G PoE+ 4SFP Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>  | JL262A#B2B |
|                | HPE Aruba Networking 2930F 48G PoE+ 4SFP Switch PDU <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>   | JL262A#B2C |
|                | HPE Aruba Networking 2930F 48G PoE+ 4SFP Switch 220v <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li></ul>  | JL262A#B2E |
|                | HPE Aruba Networking 2930F 48G PoE+ 4SFP Switch No Loc <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>   | JL262A#AC3 |

### TAA Compliant Chassis

| Rule # | Description | SKU |
|--------|-------------|-----|
|--------|-------------|-----|

### Configuration Information

|                                 |   |            |
|---------------------------------|---|------------|
| 1, 2, 3, 4,<br>5, 6, 8,<br>9,10 | HPE Aruba Networking 2930F 24G PoE+ 4SFP+ TAA-compliant Switch  | JL263A     |
|                                 | <ul style="list-style-type: none"><li>• 24 RJ-45 PoE+ autosensing 10/100/1000 ports</li><li>• 4 SFP/SFP+ 1G/10G ports</li><li>• min=0 \ max=4 SFP/SFP+ Transceivers</li><li>• 1U - Height</li></ul> |            |
|                                 | HPE Aruba Networking 2930F 24G PoE+ 4SFP+ TAA Switch PDU  | JL263A#B2B |
|                                 | <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>  |            |
|                                 | HPE Aruba Networking 2930F 24G PoE+ 4SFP+ TAA Switch PDU  | JL263A#B2C |
|                                 | <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>   |            |
|                                 | HPE Aruba Networking 2930F 24G PoE+ 4SFP+ TAA Switch 220v   | JL263A#B2E |
|                                 | <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li></ul>   |            |
|                                 | HPE Aruba Networking 2930F 24G PoE+ 4SFP+ TAA Switch No Loc   | JL263A#AC3 |
|                                 | <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>  |            |
| 1, 2, 3, 4,<br>5, 6, 8,<br>9,10 | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch   | JL559A     |
|                                 | <ul style="list-style-type: none"><li>• 48 RJ-45 PoE+ autosensing 10/100/1000 ports</li><li>• 4 SFP/SFP+ 1G/10G ports</li><li>• min=0 \ max=4 SFP/SFP+ Transceivers</li><li>• 1U - Height</li></ul> |            |
|                                 | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch PDU   | JL559A#B2B |
|                                 | <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>  |            |
|                                 | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch PDU   | JL559A#B2C |
|                                 | <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>   |            |
|                                 | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch   | JL559A#B2E |
|                                 | <ul style="list-style-type: none"><li>• United States 220 volt</li></ul>  |            |
|                                 | <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li></ul>   |            |
|                                 | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch   | JL559A#AC3 |
|                                 | <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>  |            |
| 1, 2, 3, 4,<br>5, 6, 8,<br>9,10 | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ TAA-compliant Switch  | JL264A     |
|                                 | <ul style="list-style-type: none"><li>• 48 RJ-45 PoE+ autosensing 10/100/1000 ports</li><li>• 4 SFP/SFP+ 1G/10G ports</li><li>• min=0 \ max=4 SFP/SFP+ Transceivers</li><li>• 1U - Height</li></ul> |            |
|                                 | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ TAA Switch PDU  | JL264A#B2B |
|                                 | <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (NA/MEX/TW/JP)</li></ul>  |            |
|                                 | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ TAA Switch PDU  | JL264A#B2C |
|                                 | <ul style="list-style-type: none"><li>• C15 PDU Jumper Cord (ROW)</li></ul>   |            |
|                                 | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ TAA Switch 220v   | JL264A#B2E |
|                                 | <ul style="list-style-type: none"><li>• HPE 2.3m C13 to NEMA 6-15P Power Cord(J9936A)</li></ul>   |            |
|                                 | HPE Aruba Networking 2930F 48G PoE+ 4SFP+ TAA Switch No Loc   | JL264A#AC3 |
|                                 | <ul style="list-style-type: none"><li>• No Localized Power Cord Selected</li></ul>  |            |

### Configuration Information

#### Configuration Rules

| Rule # | Description   | SKU  |
|--------|---|--|
| 1      | <p>The following Transceivers install into this Switch:</p> <p>HPE Aruba Networking 1G SFP LC SX 500m OM2 MMF Transceiver<br/>HPE Aruba Networking 1G SFP LC LX 10km SMF Transceiver<br/>HPE Aruba Networking 1G SFP LC LH 70km SMF Transceiver<br/>HPE Aruba Networking 1G SFP RJ45 T 100m Cat5e Transceiver<br/>HPE Aruba Networking 100M SFP LC FX 2km MMF Transceiver</p>   | J4858D<br>J4859D<br>J4860D<br>J8177D<br>J9054D |
| 2      | <p>The following Transceivers install into this Switch:</p> <p>HPE Aruba Networking 10G SFP+ LC SR 300m OM3 MMF Transceiver<br/>HPE Aruba Networking 10G SFP+ LC LR 10km SMF Transceiver<br/>HPE Aruba Networking 10G SFP+ LC ER 40km SMF Transceiver<br/>HPE Aruba Networking 10G SFP+ to SFP+ 1m Direct Attach Copper Cable<br/>HPE Aruba Networking 10G SFP+ to SFP+ 3m Direct Attach Copper Cable</p>   | J9150D<br>J9151E<br>J9153D<br>J9281D<br>J9283D |
| 3      | If this switch is factory installed in HPE Racks, Then the J9583A#0D1 is required.<br>CLIC Only - Allow the J9583AZ in all regions.   |  |
| 4      | Localization required on orders without #B2B, #B2C, #B2E options.   |  |
| 5      | If this Switch Chassis is selected for Rack Level Integration, Then the Switch Chassis needs to integrate (with #0D1) to the HPE Rack.  |  |
| 6      | TAA Switch Chassis are available in the US, UK, Israel, Vietnam, South Korea, India, and Taiwan only.   |  |
| 8      | <p>The following Transceivers install into this Switch:</p> <p>HPE Aruba Networking 1G SFP LC SX 500m MMF TAA Transceiver<br/>HPE Aruba Networking 1G SFP LC LX 10km SMF TAA Transceiver<br/>HPE Aruba Networking 1G SFP RJ45 T 100m Cat5e TAA Transceiver</p>  | JL745A<br>JL746A<br>JL747A                     |
| 9      | <p>The following Transceivers install into this Switch:</p> <p>HPE Aruba Networking 10G SFP+ LC SR 300m MMF TAA Transceiver<br/>HPE Aruba Networking 10G SFP+ LC LR 10km SMF TAA Transceiver</p>  | JL748A<br>JL749A                               |
| 10     | <p>Unbuildable/FAN required, generates CFGU: If order is quoted for India and contains "#B2C" Option, then Display the following:</p> <p>For BTO shipments to India:<br/>Please replace &lt;Base Model&gt;#B2C option with &lt;Base Model&gt;#AC3 in the Bill of Materials and add the appropriate INDIA PDU Power Cord below via Ad-Hoc:</p> <p>For Factory Integration of Power Cord, please add "#0D1" to the Power Cord SKU suffix. (Ex. JL671A#0D1)</p> <p>HPE Networking 2.0m C13 to C14 PDU India Power Cord<br/>HPE Networking 2.5m C15 to C14 PDU India Power Cord<br/>HPE Networking 2.5m C19 to C20 PDU India Power Cord</p> | JL671A<br>JL672A<br>JL673A                     |
| Notes: | Drop down under power supply should offer the following options and results:  |  |
|        | Switch/Router/Power Supply to PDU Power Cord - #B2B in North America, Mexico, Taiwan, and Japan or #B2C ROW. (Watson Default B2B or B2C for Rack Level CTO)   |  |
|        | Switch/Router/Power Supply to Wall Power Cord - Localized Option (Watson Default for BTO and Box Level CTO)   |  |

### Configuration Information

#AC3 - No Power Cord.

Enter the following menu selections as integrated to the CTO Model X server above if order is factory built.

### Transceivers

| Remarks                  | Description  | SKU    |
|--------------------------|--|--------|
| <b>SFP Transceivers</b>  |  |        |
|                          | HPE Aruba Networking 100M SFP LC FX 2km MMF Transceiver  | J9054D |
|                          | HPE Aruba Networking 1G SFP LC SX 500m OM2 MMF Transceiver   | J4858D |
|                          | HPE Aruba Networking 1G SFP LC LX 10km SMF Transceiver   | J4859D |
|                          | HPE Aruba Networking 1G SFP LC LH 70km SMF Transceiver   | J4860D |
|                          | HPE Aruba Networking 1G SFP RJ45 T 100m Cat5e Transceiver  | J8177D |
|                          | HPE Aruba Networking 1G SFP LC SX 500m MMF TAA Transceiver   | JL745A |
|                          | HPE Aruba Networking 1G SFP LC LX 10km SMF TAA Transceiver   | JL746A |
|                          | HPE Aruba Networking 1G SFP RJ45 T 100m Cat5e TAA Transceiver  | JL747A |
| <b>SFP+ Transceivers</b> |  |        |
|                          | HPE Aruba Networking 10G SFP+ LC SR 300m OM3 MMF Transceiver   | J9150D |
| Notes:                   | Temperature Limitations  |        |
|                          | HPE Aruba Networking 10G SFP+ LC LR 10km SMF Transceiver   | J9151E |
| Notes:                   | Temperature Limitations  |        |
|                          | HPE Aruba Networking 10G SFP+ LC ER 40km SMF Transceiver   | J9153D |
| Notes:                   | Mounting Limitations   |        |
|                          | HPE Aruba Networking 10G SFP+ LC SR 300m MMF TAA Transceiver   | JL748A |
|                          | HPE Aruba Networking 10G SFP+ LC LR 10km SMF TAA Transceiver   | JL749A |
|                          | HPE Aruba Networking 10G SFP+ to SFP+ 1m Direct Attach Copper Cable  | J9281D |
|                          | HPE Aruba Networking 10G SFP+ to SFP+ 3m Direct Attach Copper Cable  | J9283D |
| Notes:                   | Temperature limitations apply when the J9150D HPE Aruba Networking 10G SFP+ LC SR 300m OM3 MMF Transceiver or J9151E HPE Aruba Networking 10G SFP+ LC LR 10km SMF Transceiver are configured with JL693A HPE Aruba Networking 2930F 12G PoE+ 2G/2SFP+ Switch. See product installation guide for more information. |        |
|                          | Mounting limitations apply when the J9153D HPE Aruba Networking 10G SFP+ LC ER 40km SMF Transceiver is configured with a JL693A HPE Aruba Networking 2930F 12G PoE+ 2G/2SFP+ Switch. See product installation guide for more information.  |        |

### Cables

| Remarks               | Description   | SKU    |
|-----------------------|---|--------|
| <b>Console Cables</b> |   |        |
|                       | (std 0 // max 99) User Selection (min 0 // max 99) per switch |        |
|                       | HPE Aruba Networking X2C2 RJ45 to DB9 Console Cable           | JL448A |

### Configuration Information

**Notes:** Option not available for Central Managed Switch Configuration; can be ordered Separately if needed.

#### Multi-Mode Cables

|  |        |
|--|--------|
| (std 0 // max 99) User Selection (min 0 // max 99) per switch      |        |
| HPE LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable  | AJ833A |
| HPE LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable  | AJ834A |
| HPE LC to LC Multi-mode OM3 2-Fiber 2.0m 1-Pack Fiber Optic Cable  | AJ835A |
| HPE LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable  | AJ836A |
| HPE LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable | AJ837A |
| HPE LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable | AJ838A |
| HPE LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable | AJ839A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 1m Cable             | QK732A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 2m Cable             | QK733A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 5m Cable             | QK734A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 15m Cable            | QK735A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 30m Cable            | QK736A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 50m Cable            | QK737A |

**Notes:** Option not available for Central Managed Switch Configuration; can be ordered Separately if needed.

### Switch Enclosure Options

#### Mounting Kit

| Rule # | Description   | SKU    |
|--------|---|--------|
| 1, 2   | (std 0 // max 1) User Selection (min 0 // max 1) per switch<br>HPE Aruba Networking X414 1U Universal 4-post Rack Mount Kit | J9583B |

#### Configuration Rules

- If this Mounting Kit is order with #0D1 then it integrates to the HPE Universal Rack.  
(not the switch)
- This Rack Mount Kit is not compatible with JL258A, JL692A, and JL693A.

#### Accessories

|               |  |        |
|---------------|--|--------|
| <b>Notes:</b> | For JL258A and JL692A System (std 0 // max 1) User Selection (min 0 // max 1) per switch |        |
|               | HPE Aruba Networking 2930F 8-port Cable Guard  | JL311A |
|               | HPE Aruba Networking 2930F 8-port Power Shelf  | JL312A |

### Spares

#### Power Supply

|         |   |  |
|---------|---|--|
| 1, 2, 3 | For JL258A and JL692A System (std 0 // max 99) User Selection (min 0 // max 99) per switch<br>HPE Aruba Networking 2930F 8-port 54VDC 180W External Power Supply Unit<br>HPE Aruba Networking 2930F 8-port 54VDC 180W External Power Supply Unit<br>HPE Aruba Networking 2930F 8-port 54VDC 180W External Power Supply Unit<br>HPE Aruba Networking 2930F 8-port 54VDC 180W External Power Supply Unit<br>HPE Aruba Networking 2930F 8-port 54VDC 180W External Power Supply Unit | S3R22A<br>S3R22A<br>S3R22A<br>S3R22A<br>S3R22A |
|---------|---|--|

#### Configuration Rules

| Rule # | Description   | SKU |
|--------|---|-----|
| 1      | Localization required on orders without B2B, B2C, B2E or AC3 options. |     |

### Configuration Information

2 Unbuildable/FAN required, generates CFGU: If order is quoted for India and contains "#B2C" Option, then Display the following:

- For BTO shipments to India:  
Please replace <Base Model>#B2C option with <Base Model>#AC3 in the Bill of Materials and add the appropriate INDIA PDU Power Cord below via Ad-Hoc:

|   |        |
|---|--------|
| HPE Networking 2.0m C13 to C14 PDU India Power Cord | JL671A |
| HPE Networking 2.5m C15 to C14 PDU India Power Cord | JL672A |
| HPE Networking 2.5m C19 to C20 PDU India Power Cord | JL673A |

3 S3R22A External Power Supply is included with all 8-Port Switches but can be ordered as a Spare.

Notes: Drop down under power supply should offer the following options and results:

- Switch/Router/Power Supply to PDU Power Cord - #B2B in North America, Mexico, Taiwan, and Japan or #B2C ROW. (OCA Default B2B or B2C for Rack Level CTO)
- Switch/Router/Power Supply to Wall Power Cord - Localized Option (OCA Default for BTO)
- High Volt Switch/Router/Power Supply to Wall Power Cord - #B2E Option. (Offered only in North America, Mexico, Taiwan, and Japan)
- No Power Cord - #AC3 Option

### Software

#### Central

##### Cloud Services / 62XX/29XX Switch Foundation Subscriptions

|   |          |
|---|----------|
| HPE Aruba Networking Central Switch Class-2 Foundation 1 year Subscription E-STU  | Q9Y73AAE |
| HPE Aruba Networking Central Switch Class-2 Foundation 3 year Subscription E-STU  | Q9Y74AAE |
| HPE Aruba Networking Central Switch Class-2 Foundation 5 year Subscription E-STU  | Q9Y75AAE |
| HPE Aruba Networking Central Switch Class-2 Foundation 7 year Subscription E-STU  | Q9Y76AAE |
| HPE Aruba Networking Central Switch Class-2 Foundation 10 year Subscription E-STU | Q9Y77AAE |

Notes: Add the Central Cloud SKUs to the HPE Aruba Networking Catalog as Standalone:  
HPE Aruba Networking > Network Management > Central > Cloud Services

##### On-Prem Services / 62XX/29XX Switch Foundation Subscriptions

|   |          |
|---|----------|
| HPE Aruba Networking Central on Prem Switch Class-2 Foundation 1 year Subscription E-STU  | R6U78AAE |
| HPE Aruba Networking Central on Prem Switch Class-2 Foundation 3 year Subscription E-STU  | R6U79AAE |
| HPE Aruba Networking Central on Prem Switch Class-2 Foundation 5 year Subscription E-STU  | R6U80AAE |
| HPE Aruba Networking Central on Prem Switch Class-2 Foundation 7 year Subscription E-STU  | R6U81AAE |
| HPE Aruba Networking Central on Prem Switch Class-2 Foundation 10 year Subscription E-STU | R6U82AAE |

Notes: Add the Central On-Prem SKUs to the HPE Aruba Networking Catalog as Standalone:  
HPE Aruba Networking > Network Management > Central > On-Prem Services

|   |        |
|---|--------|
| HPE Aruba Networking 2930F 12G PoE+ 2G/2SFP+ Switch | JL693A |
| HPE Aruba Networking 2930F 8G PoE+ 2SFP+ Switch     | JL258A |

##### FedRAMP Services / 62XX/29XX Switch Foundation Subscriptions

|  |          |
|--|----------|
| HPE Aruba Networking Central 62xx or 29xx Switch Foundation Government 1-year Subscription E-STU | R8K94AAE |
|--|----------|

### Configuration Information

|   |          |
|---|----------|
| HPE Aruba Networking Central 62xx or 29xx Switch Foundation Government 3-year Subscription E-STU  | R8K95AAE |
| HPE Aruba Networking Central 62xx or 29xx Switch Foundation Government 5-year Subscription E-STU  | R8K96AAE |
| HPE Aruba Networking Central 62xx or 29xx Switch Foundation Government 7-year Subscription E-STU  | R8K97AAE |
| HPE Aruba Networking Central 62xx or 29xx Switch Foundation Government 10-year Subscription E-STU | R8K98AAE |

**Notes:** Add the Central FedRAMP Service SKUs to the HPE Aruba Networking Catalog as Standalone:  
HPE Aruba Networking > Network Management > Central > FedRAMP

### On-Prem Services / 62XX/29XX Switch Advanced Subscriptions

|  |          |
|--|----------|
| HPE Aruba Networking Central On-Premises Switch Class2 Advanced 1-year Subscription E-STU  | R6U98AAE |
| HPE Aruba Networking Central On-Premises Switch Class2 Advanced 3-year Subscription E-STU  | R6U99AAE |
| HPE Aruba Networking Central On-Premises Switch Class2 Advanced 5-year Subscription E-STU  | R6V00AAE |
| HPE Aruba Networking Central On-Premises Switch Class2 Advanced 7-year Subscription E-STU  | R6V01AAE |
| HPE Aruba Networking Central On-Premises Switch Class2 Advanced 10-year Subscription E-STU | R6V02AAE |

**Notes:** Add the Central On-Prem SKUs to the HPE Aruba Networking Catalog as Standalone:  
HPE Aruba Networking > Network Management > Central > On-Prem Services

### As-a-Service

#### HPE Aruba Networking Central

##### Cloud Services / 62XX/29XX Switch Foundation Subscriptions

|   |  |          |
|---|--|----------|
| 2 | HPE Aruba Networking Central Switch Class-2 Foundation 1 year Subscription SaaS  | Q9Y73AAS |
| 2 | HPE Aruba Networking Central Switch Class-2 Foundation 3 year Subscription SaaS  | Q9Y74AAS |
| 2 | HPE Aruba Networking Central Switch Class-2 Foundation 5 year Subscription SaaS  | Q9Y75AAS |
| 2 | HPE Aruba Networking Central Switch Class-2 Foundation 7 year Subscription SaaS  | Q9Y76AAS |
| 2 | HPE Aruba Networking Central Switch Class-2 Foundation 10 year Subscription SaaS | Q9Y77AAS |

##### Cloud Services / Switch Advanced AAS Licenses

|   |  |          |
|---|--|----------|
| 7 | HPE Aruba Networking Central Switch Class-2 Advanced 1 year Subscription SaaS  | S0W72AAS |
| 7 | HPE Aruba Networking Central Switch Class-2 Advanced 3 year Subscription SaaS  | S0W73AAS |
| 7 | HPE Aruba Networking Central Switch Class-2 Advanced 5 year Subscription SaaS  | S0W74AAS |
| 7 | HPE Aruba Networking Central Switch Class-2 Advanced 7 year Subscription SaaS  | S0W75AAS |
| 7 | HPE Aruba Networking Central Switch Class-2 Advanced 10 year Subscription SaaS | S0W76AAS |

##### Configuration Rules

| Rule# | Description   | SKU |
|-------|---|-----|
| 2     | Add the Central Cloud SKUs to the HPE Aruba Networking Catalog as Standalone:<br>HPE Aruba Networking > Network Management > Central > Cloud Services |     |
| 7     | For IRIS reference only. No action required for OCX and Clic  |     |

### Technical Specifications

#### HPE Aruba Networking 2930F 8-port Cable Guard (JL311A)

The Cable Guard secures cables that are connected to the switch and provides extra security against theft or tampering with the switch and its cables after it is installed

|                                 |  |
|---------------------------------|--|
| <b>Product Type</b>             | Mounting Kit   |
| <b>Physical characteristics</b> | <b>Dimensions:</b> 1.42(w) x 4.33(d) x 0.69(h) in (3.6 x 11 x 1.75 cm)<br><b>Weight:</b> 1.28 lb (0.58 kg)   |
| <b>Notes</b>                    | <b>Dimensions:</b> 10.94" x 3.62" x 1.69" or 27.8cm x 9.2cm x 4.3cm w/ears 10.94" x 1.69" x 1.69" or 27.8cm x 4.3cm x 4.3cm without ears<br><b>Weight:</b> 1.262 lbs or 57 kg (including faceplate, ears, and screws) 1.026 lbs or .47 kg (faceplate only)   |
| <b>Warranty Services</b>        | Limited Lifetime Warranty:<br>Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office. |

#### HPE Aruba Networking 2930F 8-port Power Shelf (JL312A)

An easy-to-use solution for attaching the external power adapter to any of the HPE Aruba Networking 2530 8-port switches.

|                                      |  |
|--------------------------------------|--|
| <b>Product Type</b>                  | Mounting Kit   |
| <b>Physical characteristics</b>      | <b>Dimensions:</b> 10.75(w) x 6(d) x 2(h) in (27.31 x 15.24 x 5.08 cm)<br><b>Weight:</b> 0.93 lb (0.42 kg)   |
| <b>Overall Positioning Statement</b> | The HPE Aruba Networking 2930F 8-port Power Shelf provides an easy to use solution for attaching the external power adapter to the HPE Aruba Networking 2930F 8G 2SFP+ PoE+ Switch. The power adapter shelf can be quickly attached on the rear of the HPE Aruba Networking 2930F 8G PoE+ 2SFP+ Switch and the adapter fit into place. This power adapter shelf is designed for wall, table or rack deployments. |
| <b>Key Features</b>                  | Quickly attach external power adapter to 8 port switch<br>Designed for use with HPE Aruba Networking 2930F 8G PoE+ 2SFP+ Switch  |
| <b>Notes</b>                         | The HPE Aruba Networking 2930F 8-port Power Shelf is an accessory for the HPE Aruba Networking 2930F 8G PoE+ 2SFP+ Switch. The shelf mounts on the back of the switch providing a place to hold the external power adapter.  |
| <b>Warranty Services</b>             | Limited Lifetime Warranty:<br>Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.                                   |

#### HPE Aruba Networking 2930F 24G 4SFP+ Switch (JL253A)

|                                   |  |
|-----------------------------------|--|
| <b>I/O ports and slots</b>        | 24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)<br>Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only<br>4 SFP+ 1/10GbE ports; PHY-less |
| <b>Additional ports and slots</b> | 1 dual-personality (RJ-45 or USB micro-B) serial console port  |

### Technical Specifications

|  |  |  |
|--|--|--|
| <b>Physical characteristics</b>  | <b>Dimensions</b>  | 17.42(w) x 7.88(d) x 1.73(h) in (44.25 x 20.02 x 4.39 cm)<br>(1U height)                 |
|  | <b>Weight</b>  | 5.31 lb (2.41 kg)  |
| <b>Memory and processor</b>  | Dual Core ARM Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB<br>4.5MB Ingress/7.875MB Egress, 4 GB eMMC   |  |
| <b>Performance</b>   | <b>1000 Mb Latency</b>   | < 3.8 µs (64-byte packets)   |
|  | <b>10 Gbps Latency</b>   | < 2.9 µs (64-byte packets)   |
|  | <b>Throughput</b>  | up to 95.2 Mpps  |
|  | <b>Switching capacity</b>  | 128 Gbps   |
| <b>Performance</b>   | <b>Routing table size</b>  | 2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP                     |
|  | <b>MAC address table size</b>  | 32768 entries  |
| <b>Environment</b>   | <b>Operating temperature</b>   | 32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet |
|  | <b>Operating relative humidity</b>   | 15% to 95% @ 104°F (40°C), noncondensing   |
|  | <b>Non-operating/Storage temperature</b>   | -40°F to 158°F (-40°C to 70°C); up to 15000 Feet   |
|  | <b>Non-operating/Storage temperature</b>   | 15% to 95% @ 149°F (65°C), noncondensing   |
|  | <b>Acoustic</b>  | Power: 49.7 dB, Pressure: 37.1 dB  |
|  | <b>Airflow direction</b>   | Side-to-side   |
| <b>Electrical characteristics</b>  | <b>Maximum heat dissipation</b>  | 100.0 BTU/hr (105.5 kJ/hr)   |
|  | <b>Voltage</b>   | 100 - 127 / 200 - 240 VAC, rated   |
|  | <b>Current</b>   | 0.6/0.4 A  |
|  | <b>Maximum power rating</b>  | 29.3 W   |
|  | <b>Idle power</b>  | 19.5 W   |
|  | <b>Frequency</b>   | 50/60 Hz   |
| <p><b>Notes:</b></p> <p>Idle power is the actual power consumption of the device with no ports connected.</p> <p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p> |  |  |
| <b>Safety</b>  | UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1   |  |
| <b>Emissions</b>   | EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438  |  |
| <b>Management</b>  | HPE Aruba Networking Central; HPE Aruba Networking Management Software (AirWave); IMC - Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP   |  |
| <b>Services</b>  | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office. |  |
| <b>Immunity</b>  | <b>Generic</b>   | EN 55024:2010/CISPR 24   |
|  | <b>ESD</b>   | IEC 61000-4-2  |
|  | <b>Radiated</b>  | IEC 61000-4-3  |
| <b>Immunity</b>  | <b>EFT/Burst</b>   | IEC 61000-4-4  |

### Technical Specifications

|                                       |                  |
|---------------------------------------|------------------|
| <b>Surge</b>                          | IEC 61000-4-5    |
| <b>Conducted</b>                      | IEC 61000-4-6    |
| <b>Power frequency magnetic field</b> | IEC 61000-4-8    |
| <b>Voltage dips and interruptions</b> | IEC 61000-4-11   |
| <b>Harmonics</b>                      | IEC/EN 61000-3-2 |
| <b>Flicker</b>                        | IEC/EN 61000-3-3 |

### HPE Aruba Networking 2930F 48G 4SFP+ Switch (JL254A)

|   |  |  |
|---|--|--|
| <b>I/O ports and slots</b>  | 48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only<br>4 SFP+ 1/10GbE ports; PHY-less |  |
| <b>Additional ports and slots</b>   | 1 dual-personality (RJ-45 or USB micro-B) serial console port  |  |
| <b>Physical characteristics</b>   | <b>Dimensions</b>  | 17.42(w) x 9.7(d) x 1.73(h) in (44.25 x 24.63 x 4.39 cm)<br>(1U height)                  |
|   | <b>Weight</b>  | 6.83 lb (3.10 kg)  |
| <b>Memory and processor</b>   | Dual Core ARM Cortex @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.875MB Egress, 4 GB eMMC   |  |
| <b>Performance</b>  | <b>1000 Mb Latency</b>   | < 3.8 µs (64-byte packets)   |
|   | <b>10 Gbps Latency</b>   | < 2.9 µs (64-byte packets)   |
|   | <b>Throughput</b>  | up to 112.0 Mpps   |
|   | <b>Switching capacity</b>  | 176 Gbps   |
|   | <b>Routing table size</b>  | 2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP                     |
|   | <b>MAC address table size</b>  | 32768 entries  |
| <b>Environment</b>  | <b>Operating temperature</b>   | 32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet |
|   | <b>Operating relative humidity</b>   | 15% to 95% @ 104°F (40°C), noncondensing   |
|   | <b>Non-operating/Storage temperature</b>   | -40°F to 158°F (-40°C to 70°C); up to 15000 Feet   |
|   | <b>Non-operating/Storage temperature</b>   | 15% to 95% @ 149°F (65°C), noncondensing   |
|   | <b>Acoustic</b>  | Power: 54.1 dB, Pressure: 40.2 dB  |
|   | <b>Airflow direction</b>   | Side-to-side   |
| <b>Electrical characteristics</b>   | <b>Maximum heat dissipation</b>  | 157.2 BTU/hr (165.8 KJ/hr)   |
|   | <b>Voltage</b>   | 100 - 127 / 200 - 240 VAC, rated   |
|   | <b>Current</b>   | 0.9/0.6 A  |
|   | <b>Maximum power rating</b>  | 46.6 W   |
|   | <b>Idle power</b>  | 32.7 W   |
|   | <b>Frequency</b>   | 50/60 Hz   |
| <b>Notes:</b>   |  |  |
| Idle power is the actual power consumption of the device with no ports connected.   |  |  |
| Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if |  |  |

### Technical Specifications

|                   |  |                        |
|-------------------|--|------------------------|
|                   | equipped), 100% traffic, all ports plugged in, and all modules populated.  |                        |
| <b>Safety</b>     | UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1   |                        |
| <b>Emissions</b>  | EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438  |                        |
| <b>Immunity</b>   | <b>Generic</b>   | EN 55024:2010/CISPR 24 |
|                   | <b>ESD</b>   | IEC 61000-4-2          |
|                   | <b>Radiated</b>  | IEC 61000-4-3          |
|                   | <b>EFT/Burst</b>   | IEC 61000-4-4          |
|                   | <b>Surge</b>   | IEC 61000-4-5          |
|                   | <b>Conducted</b>   | IEC 61000-4-6          |
|                   | <b>Power frequency magnetic field</b>  | IEC 61000-4-8          |
|                   | <b>Voltage dips and interruptions</b>  | IEC 61000-4-11         |
|                   | <b>Harmonics</b>   | IEC/EN 61000-3-2       |
| <b>Immunity</b>   | <b>Flicker</b>   | IEC/EN 61000-3-3       |
| <b>Management</b> | HPE Aruba Networking Central; HPE Aruba Networking Management Software (AirWave); IMC - Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP   |                        |
| <b>Services</b>   | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office. |                        |

### HPE Aruba Networking 2930F 24G PoE+ 4SFP+ Switch (JL255A)

|                                   |  |   |
|-----------------------------------|--|---|
| <b>I/O ports and slots</b>        | 24 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only<br>4 SFP+ 1/10GbE ports; PHY-less |   |
| <b>Additional ports and slots</b> | 1 dual-personality (RJ-45 or USB micro-B) serial console port  |   |
| <b>Physical characteristics</b>   | <b>Dimensions</b>  | 17.42(w) x 11.98(d) x 1.73(h) in (44.25 x 30.42 x 4.39 cm) (1U height)                  |
|                                   | <b>Weight</b>  | 8.6 lb (3.9 kg)   |
| <b>Memory and processor</b>       | Dual Core ARM Cortex @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5 MB Ingress/7.875MB Egress, 4 GB eMMC  |   |
| <b>Performance</b>                | <b>1000 Mb Latency</b>   | < 3.8 µs (64-byte packets)  |
|                                   | <b>10 Gbps Latency</b>   | < 2.9 µs (64-byte packets)  |
|                                   | <b>Throughput</b>  | up to 95.2 Mpps   |
|                                   | <b>Switching capacity</b>  | 128 Gbps  |
|                                   | <b>Routing table size</b>  | 2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP                    |
|                                   | <b>MAC address table size</b>  | 32768 entries   |
| <b>Environment</b>                | <b>Operating temperature</b>   | 32°F to 113°F (0°C to 45°C); up to 5000 Feet, -0C to 40C (32F to 104F) up to 10000 Feet |
|                                   | <b>Operating relative humidity</b>   | 15% to 95% @ 104°F (40°C), noncondensing  |

### Technical Specifications

|   |  |  |
|---|--|--|
|   | <b>Non-operating/Storage temperature</b>   | -40°F to 158°F (-40°C to 70°C); up to 15000 Feet |
|   | <b>Non-operating/Storage temperature</b>   | 15% to 95% @ 149°F (65°C), noncondensing         |
|   | <b>Acoustic</b>  | Power: 54.1 dB, Pressure: 40.2 dB                |
|   | <b>Airflow direction</b>   | Side-to-side                                     |
| <b>Electrical characteristics</b>   | <b>Power efficiency certifications</b>   | 80plus.org certification: Silver                 |
|   | <b>Maximum heat dissipation</b>  | 258.0 BTU/hr (272.2 KJ/hr)                       |
|   | <b>Voltage</b>   | 100 - 127 / 200 - 240 VAC, rated                 |
|   | <b>Current</b>   | 4.9/2.4 A  |
|   | <b>Maximum power rating</b>  | 445 W  |
|   | <b>Idle power</b>  | 36.8 W   |
|   | <b>PoE power</b>   | 370 W PoE+                                       |
|   | <b>Frequency</b>   | 50/60 Hz   |
| <b>Notes:</b>   |  |  |
| Idle power is the actual power consumption of the device with no ports connected.   |  |  |
| Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |  |  |
| <b>Safety</b>   | UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1   |  |
| <b>Emissions</b>  | EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438  |  |
| <b>Immunity</b>   | <b>Generic</b>   | EN 55024:2010/CISPR 24                           |
|   | <b>ESD</b>   | IEC 61000-4-2                                    |
|   | <b>Radiated</b>  | IEC 61000-4-3                                    |
|   | <b>EFT/Burst</b>   | IEC 61000-4-4                                    |
|   | <b>Surge</b>   | IEC 61000-4-5                                    |
|   | <b>Conducted</b>   | IEC 61000-4-6                                    |
|   | <b>Power frequency magnetic field</b>  | IEC 61000-4-8                                    |
|   | <b>Voltage dips and interruptions</b>  | IEC 61000-4-11                                   |
|   | <b>Harmonics</b>   | IEC/EN 61000-3-2                                 |
|   | <b>Flicker</b>   | IEC/EN 61000-3-3                                 |
| <b>Management</b>   | HPE Aruba Networking Central; HPE Aruba Networking Management Software (AirWave); IMC - Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP   |  |
| <b>Services</b>   | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office. |  |

**HPE Aruba Networking 2930F 48G PoE+ 4SFP+ Switch (JL256A, JL256ACM)<sup>1</sup>**

### Technical Specifications

|                                   |  |   |
|-----------------------------------|--|---|
| <b>I/O ports and slots</b>        | 48 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only<br>4 SFP+ 1/10GbE ports; PHY-less   |   |
| <b>Additional ports and slots</b> | 1 dual-personality (RJ-45 or USB micro-B) serial console port  |   |
| <b>Physical characteristics</b>   | <b>Dimensions</b>  | 17.42(w) x 11.98(d) x 1.73(h) in (44.25 x 30.42 x 4.39 cm) (1U height)                  |
|                                   | <b>Weight</b>  | 9.83 lb (4.46 kg)   |
| <b>Memory and processor</b>       | Dual Core ARM Cortex @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.875MB Egress, 4 GB eMMC   |   |
| <b>Performance</b>                | <b>1000 Mb Latency</b>   | < 3.8 µs (64-byte packets)  |
|                                   | <b>10 Gbps Latency</b>   | < 2.9 µs (64-byte packets)  |
|                                   | <b>Throughput</b>  | up to 112.0 Mpps  |
|                                   | <b>Switching capacity</b>  | 176 Gbps  |
|                                   | <b>Routing table size</b>  | 2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP                    |
|                                   | <b>MAC address table size</b>  | 32768 entries   |
| <b>Environment</b>                | <b>Operating temperature</b>   | 32°F to 113°F (0°C to 45°C); up to 5000 Feet, -0C to 40C (32F to 104F) up to 10000 Feet |
|                                   | <b>Operating relative humidity</b>   | 15% to 95% @ 104°F (40°C), noncondensing  |
|                                   | <b>Non-operating/Storage temperature</b>   | -40°F to 158°F (-40°C to 70°C); up to 15000 Feet  |
|                                   | <b>Non-operating/Storage temperature</b>   | 15% to 95% @ 149°F (65°C), noncondensing  |
|                                   | <b>Acoustic</b>  | Power: 55.7 dB, Pressure: 41.7 dB   |
| <b>Environment</b>                | <b>Airflow direction</b>   | Side-to-side  |
| <b>Electrical characteristics</b> | <b>Power efficiency certifications</b>   | 80plus.org certification: Silver  |
|                                   | <b>Maximum heat dissipation</b>  | 293.0 BTU/hr (309.1 kJ/hr)  |
|                                   | <b>Voltage</b>   | 100 - 127 / 200 - 240 VAC, rated  |
|                                   | <b>Current</b>   | 5.1/2.5 A   |
|                                   | <b>Maximum power rating</b>  | 459 W   |
|                                   | <b>Idle power</b>  | 48.6 W  |
|                                   | <b>PoE power</b>   | 370 W PoE+  |
|                                   | <b>Frequency</b>   | 50/60 Hz  |
| <b>Electrical characteristics</b> | <p><b>Notes:</b></p> <p>Idle power is the actual power consumption of the device with no ports connected.</p> <p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p> |   |
| <b>Safety</b>                     | UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1   |   |
| <b>Emissions</b>                  | EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438  |   |
| <b>Immunity</b>                   | <b>Generic</b>   | EN 55024:2010/CISPR 24  |

### Technical Specifications

|                                       |   |
|---------------------------------------|---|
| <b>ESD</b>                            | IEC 61000-4-2   |
| <b>Radiated</b>                       | IEC 61000-4-3   |
| <b>EFT/Burst</b>                      | IEC 61000-4-4   |
| <b>Surge</b>                          | IEC 61000-4-5   |
| <b>Conducted</b>                      | IEC 61000-4-6   |
| <b>Power frequency magnetic field</b> | IEC 61000-4-8   |
| <b>Voltage dips and interruptions</b> | IEC 61000-4-11  |
| <b>Harmonics</b>                      | IEC/EN 61000-3-2  |
| <b>Flicker</b>                        | IEC/EN 61000-3-3  |
| <b>Management</b>                     | HPE Aruba Networking Central; HPE Aruba Networking Management Software (AirWave); IMC - Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP  |
| <b>Services</b>                       | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.  |
| <b>Notes:</b>                         | <sup>1</sup> All hardware SKUs can be managed by HPE Aruba Networking Central. Central Managed (CM) SKUs are used for simplified ordering within U.S. and Canada only. Append "CM" to the indicated SKU #: (e.g., JL261ACM to order the JL261A). Requires an active Central license and end-user information consistent with the Central license purchase. Applicable accessories with a valid "CM" suffix should also be placed on the same order. |

### HPE Aruba Networking 2930F 8G PoE+ 2SFP+ Switch (JL258A, JL258ACM) <sup>1</sup>

|                                   |   |  |
|-----------------------------------|---|--|
| <b>I/O ports and slots</b>        | 8 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only<br>2 SFP+ 1/10GbE ports; PHY-less |  |
| <b>Additional ports and slots</b> | 1 dual-personality (RJ-45 or USB micro-B) serial console port   |  |
| <b>Physical characteristics</b>   | <b>Dimensions</b>   | 10(w) x 10(d) x 1.73(h) in (25.4 x 25.4 x 4.39 cm) (1U height)                           |
|                                   | <b>Weight</b>   | 4.41 lb (2.0 kg)   |
| <b>Memory and processor</b>       | Dual Core ARM Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB<br>4.5MB Ingress/7.785 Egress, 4 GB eMMC  |  |
| <b>Performance</b>                | <b>1000 Mb Latency</b>  | < 3.8 µs (64-byte packets)   |
|                                   | <b>10 Gbps Latency</b>  | < 2.9 µs (64-byte packets)   |
| <b>Performance</b>                | <b>Throughput</b>   | up to 41.7 Mpps  |
|                                   | <b>Switching capacity</b>   | 56 Gbps  |
|                                   | <b>Routing table size</b>   | 2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP                     |
|                                   | <b>MAC address table size</b>   | 32768 entries  |
| <b>Environment</b>                | <b>Operating temperature</b>  | 32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet |
|                                   | <b>Operating relative humidity</b>  | 15% to 95% @ 104°F (40°C), noncondensing   |

### Technical Specifications

|   |  |  |
|---|--|--|
| <b>Environment</b>  | <b>Non-operating/Storage temperature</b>   | -40°F to 158°F (-40°C to 70°C); up to 15000 Feet |
|   | <b>Non-operating/Storage temperature</b>   | 15% to 95% @ 149°F (65°C), noncondensing         |
|   | <b>Acoustic</b>  | Power: 0 dB, Pressure: 0 dB Fanless              |
| <b>Electrical characteristics</b>   | <b>Power efficiency certifications</b>   | DoE VI certification.                            |
|   | <b>Maximum heat dissipation</b>  | 58.6 BTU/hr (61.8 kJ/hr)                         |
|   | <b>Voltage</b>   | 90 - 264 VAC, rated                              |
|   | <b>Current</b>   | 2.6 A  |
|   | <b>Maximum power rating</b>  | 155 W  |
|   | <b>PoE power</b>   | 125 W PoE+                                       |
|   | <b>Frequency</b>   | 50/60 Hz   |
| <b>Notes:</b>   |  |  |
| Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |  |  |
| PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of a External Power Supply (EPS).   |  |  |
| <b>Safety</b>   | UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1   |  |
| <b>Emissions</b>  | EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438  |  |
| <b>Immunity</b>   | <b>Generic</b>   | EN 55024:2010/CISPR 24                           |
|   | <b>ESD</b>   | IEC 61000-4-2                                    |
|   | <b>Radiated</b>  | IEC 61000-4-3                                    |
|   | <b>EFT/Burst</b>   | IEC 61000-4-4                                    |
|   | <b>Surge</b>   | IEC 61000-4-5                                    |
|   | <b>Conducted</b>   | IEC 61000-4-6                                    |
|   | <b>Power frequency magnetic field</b>  | IEC 61000-4-8                                    |
|   | <b>Voltage dips and interruptions</b>  | IEC 61000-4-11                                   |
|   | <b>Harmonics</b>   | IEC/EN 61000-3-2                                 |
|   | <b>Flicker</b>   | IEC/EN 61000-3-3                                 |
| <b>Management</b>   | HPE Aruba Networking Central; HPE Aruba Networking Management Software (AirWave); IMC - Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP   |  |
| <b>Services</b>   | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.   |  |
| <b>Notes:</b>   | 1 All hardware SKUs can be managed by HPE Aruba Networking Central. Central Managed (CM) SKUs are used for simplified ordering within U.S. and Canada only. Append "CM" to the indicated SKU #: (e.g., JL261ACM to order the JL261A). Requires an active Central license and end-user information consistent with the Central license purchase. Applicable accessories with a valid "CM" suffix should also be placed on the |  |

### Technical Specifications

same order.

| HPE Aruba Networking 2930F 8G PoE+ 2SFP+ TAA-compliant Switch (JL692A)  |   |  |
|---|---|--|
| I/O ports and slots   | 8 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only<br>2 SFP+ 1/10GbE ports; PHY-less |  |
| Additional ports and slots  | 1 dual-personality (RJ-45 or USB micro-B) serial console port   |  |
| Physical characteristics  | Dimensions  | 10(w) x 10(d) x 1.73(h) in (25.4 x 25.4 x 4.39 cm) (1U height)                           |
|   | Weight  | 4.41 lb (2.0 kg)   |
| Memory and processor  | Dual Core ARM Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB<br>4.5MB Ingress/7.785 Egress, 4 GB eMMC  |  |
| Performance   | 1000 Mb Latency   | < 3.8 µs (64-byte packets)   |
|   | 10 Gbps Latency   | < 2.9 µs (64-byte packets)   |
|   | Throughput  | up to 41.7 Mpps  |
|   | Switching capacity  | 56 Gbps  |
|   | Routing table size  | 2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP                     |
|   | MAC address table size  | 32768 entries  |
| Environment   | Operating temperature   | 32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet |
|   | Operating relative humidity   | 15% to 95% @ 104°F (40°C), noncondensing   |
| Environment   | Non-operating/Storage temperature   | -40°F to 158°F (-40°C to 70°C); up to 15000 Feet   |
|   | Non-operating/Storage temperature   | 15% to 95% @ 149°F (65°C), noncondensing   |
|   | Acoustic  | Power: 0 dB, Pressure: 0 dB Fanless  |
| Electrical characteristics  | Power efficiency certifications   | DoE VI certification.  |
|   | Maximum heat dissipation  | 58.6 BTU/hr (61.8 kJ/hr)   |
|   | Voltage   | 90 - 264 VAC, rated  |
|   | Current   | 2.6 A  |
|   | Maximum power rating  | 155 W  |
|   | PoE power   | 125 W PoE+   |
|   | Frequency   | 50/60 Hz   |
| <b>Notes:</b>   |   |  |
| Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |   |  |
| PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of a External Power Supply (EPS).   |   |  |

### Technical Specifications

|                   |  |                        |
|-------------------|--|------------------------|
| <b>Safety</b>     | UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1   |                        |
| <b>Emissions</b>  | EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438  |                        |
| <b>Immunity</b>   | <b>Generic</b>   | EN 55024:2010/CISPR 24 |
|                   | <b>ESD</b>   | IEC 61000-4-2          |
|                   | <b>Radiated</b>  | IEC 61000-4-3          |
|                   | <b>EFT/Burst</b>   | IEC 61000-4-4          |
|                   | <b>Surge</b>   | IEC 61000-4-5          |
|                   | <b>Conducted</b>   | IEC 61000-4-6          |
|                   | <b>Power frequency magnetic field</b>  | IEC 61000-4-8          |
|                   | <b>Voltage dips and interruptions</b>  | IEC 61000-4-11         |
| <b>Immunity</b>   | <b>Harmonics</b>   | IEC/EN 61000-3-2       |
|                   | <b>Flicker</b>   | IEC/EN 61000-3-3       |
| <b>Management</b> | HPE Aruba Networking Central; HPE Aruba Networking Management Software (AirWave); IMC - Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP   |                        |
| <b>Services</b>   | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.   |                        |
| <b>Notes:</b>     | 1 All hardware SKUs can be managed by HPE Aruba Networking Central. Central Managed (CM) SKUs are used for simplified ordering within U.S. and Canada only. Append "CM" to the indicated SKU #: (e.g., JL261ACM to order the JL261A). Requires an active Central license and end-user information consistent with the Central license purchase. Applicable accessories with a valid "CM" suffix should also be placed on the same order. |                        |

### HPE Aruba Networking 2930F 12G PoE+ 2G/2SFP+ Switch (JL693A)

|                                   |  |   |
|-----------------------------------|--|---|
| <b>I/O ports and slots</b>        | 12 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only |   |
|                                   | 2 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only                          |   |
|                                   | 2 SFP+ 1/10GbE ports; PHY-less   |   |
| <b>Additional ports and slots</b> | 1 dual-personality (RJ-45 or USB micro-B) serial console port  |   |
| <b>Physical characteristics</b>   | <b>Dimensions</b>  | 10 (w) x 10 (d) x 1.73 (h) in (25.4 x 25.4 x 4.39 cm) (1U height) |
|                                   | <b>Weight</b>  | 4.85 lb (2.2kg)   |
| <b>Memory and processor</b>       | Dual Core ARM Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB<br>4.5MB Ingress/7.785 Egress, 4 GB eMMC   |   |
| <b>Performance</b>                | <b>1000 Mb Latency</b>   | < 3.8 µs (64-byte packets)  |
|                                   | <b>10 Gbps Latency</b>   | < 2.9 µs (64-byte packets)  |

### Technical Specifications

|                                   |  |  |
|-----------------------------------|--|--|
|                                   | <b>Throughput</b>                        | up to 41.7 Mpps  |
|                                   | <b>Switching capacity</b>                | 68 Gbps  |
|                                   | <b>Routing table size</b>                | 2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP                     |
|                                   | <b>MAC address table size</b>            | 32768 entries  |
| <b>Environment</b>                | <b>Operating temperature</b>             | 32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet |
|                                   | <b>Operating relative humidity</b>       | 15% to 95% @ 104°F (40°C), noncondensing   |
|                                   | <b>Non-operating/Storage temperature</b> | -40°F to 158°F (-40°C to 70°C); up to 15000 Feet   |
|                                   | <b>Non-operating/Storage temperature</b> | 15% to 95% @ 149°F (65°C), noncondensing   |
|                                   | <b>Acoustic</b>                          | Power: 0 dB, Pressure: 0 dB Fanless  |
| <b>Electrical characteristics</b> | <b>Power efficiency certifications</b>   | meets DoE VI certification.  |
|                                   | <b>Maximum heat dissipation</b>          | 68.2 BTU/hr (72.0 kJ/hr)   |
|                                   | <b>Voltage</b>                           | 90 - 264 VAC, rated  |
|                                   | <b>Current</b>                           | 1.7 A  |
|                                   | <b>Maximum power rating</b>              | 170 W  |
|                                   | <b>PoE power</b>                         | 139 W PoE+   |
|                                   | <b>Frequency</b>                         | 50/60 Hz   |

|                  |  |                        |
|------------------|--|------------------------|
|                  | <b>Notes:</b>  |                        |
|                  | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.                          |                        |
|                  | PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of a External Power Supply (EPS).  |                        |
| <b>Safety</b>    | UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1 |                        |
| <b>Emissions</b> | EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438  |                        |
| <b>Immunity</b>  | <b>Generic</b>   | EN 55024:2010/CISPR 24 |
|                  | <b>ESD</b>   | IEC 61000-4-2          |
|                  | <b>Radiated</b>  | IEC 61000-4-3          |
|                  | <b>EFT/Burst</b>   | IEC 61000-4-4          |
|                  | <b>Surge</b>   | IEC 61000-4-5          |
|                  | <b>Conducted</b>   | IEC 61000-4-6          |
|                  | <b>Power frequency magnetic field</b>  | IEC 61000-4-8          |
|                  | <b>Voltage dips and interruptions</b>  | IEC 61000-4-11         |
|                  | <b>Harmonics</b>   | IEC/EN 61000-3-2       |
|                  | <b>Flicker</b>   | IEC/EN 61000-3-3       |

### Technical Specifications

|                   |  |
|-------------------|--|
| <b>Management</b> | HPE Aruba Networking Central; HPE Aruba Networking Management Software (AirWave); IMC - Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP   |
| <b>Services</b>   | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office. |

| HPE Aruba Networking 2930F 24G 4SFP Switch (JL259A) |   |   |
|---|---|---|
| <b>I/O ports and slots</b>                          | 24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only<br>4 SFP |   |
| <b>Additional ports and slots</b>                   | 1 dual-personality (RJ-45 or USB micro-B) serial console port   |   |
| <b>Physical characteristics</b>                     | <b>Dimensions</b>   | 17.42(w) x 7.88(d) x 1.73(h) in (44.25 x 20.02 x 4.39 cm)<br>(1U height)  |
|   | <b>Weight</b>   | 5.31 lb (2.41 kg)   |
| <b>Memory and processor</b>                         | Dual Core ARM Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB<br>4.5MB Ingress/7.785 Egress, 4 GB eMMC  |   |
| <b>Performance</b>                                  | <b>1000 Mb Latency</b>  | < 3.8 µs (64-byte packets)  |
|   | <b>Throughput</b>   | up to 41.7 Mpps   |
|   | <b>Switching capacity</b>   | 56 Gbps   |
|   | <b>Routing table size</b>   | 2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP  |
|   | <b>MAC address table size</b>   | 32768 entries   |
| <b>Environment</b>                                  | <b>Operating temperature</b>  | 32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet  |
|   | <b>Operating relative humidity</b>  | 15% to 95% @ 104°F (40°C), noncondensing  |
|   | <b>Non-operating/Storage temperature</b>  | -40°F to 158°F (-40°C to 70°C); up to 15000 Feet  |
|   | <b>Non-operating/Storage temperature</b>  | 15% to 95% @ 149°F (65°C), noncondensing  |
|   | <b>Acoustic</b>   | Power: 49.7 dB, Pressure: 37.1 dB   |
|   | <b>Airflow direction</b>  | Side-to-side  |
| <b>Electrical characteristics</b>                   | <b>Maximum heat dissipation</b>   | 100.0 BTU/hr (105.5 kJ/hr)  |
|   | <b>Voltage</b>  | 100 - 127 / 200 - 240 VAC, rated  |
|   | <b>Current</b>  | 0.6/0.4 A   |
|   | <b>Maximum power rating</b>   | 29.3 W  |
| <b>Electrical characteristics</b>                   | <b>Idle power</b>   | 19.5 W  |
|   | <b>Frequency</b>  | 50/60 Hz  |
|   | <b>Notes:</b>   | Idle power is the actual power consumption of the device with no ports connected.   |
|   |   | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |

### Technical Specifications

|                   |  |                        |
|-------------------|--|------------------------|
| <b>Safety</b>     | UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1   |                        |
| <b>Emissions</b>  | EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438  |                        |
| <b>Immunity</b>   | <b>Generic</b>   | EN 55024:2010/CISPR 24 |
|                   | <b>ESD</b>   | IEC 61000-4-2          |
|                   | <b>Radiated</b>  | IEC 61000-4-3          |
|                   | <b>EFT/Burst</b>   | IEC 61000-4-4          |
|                   | <b>Surge</b>   | IEC 61000-4-5          |
|                   | <b>Conducted</b>   | IEC 61000-4-6          |
|                   | <b>Power frequency magnetic field</b>  | IEC 61000-4-8          |
|                   | <b>Voltage dips and interruptions</b>  | IEC 61000-4-11         |
|                   | <b>Harmonics</b>   | IEC/EN 61000-3-2       |
|                   | <b>Flicker</b>   | IEC/EN 61000-3-3       |
| <b>Management</b> | HPE Aruba Networking Central; HPE Aruba Networking Management Software (AirWave); IMC - Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP   |                        |
| <b>Services</b>   | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office. |                        |

### HPE Aruba Networking 2930F 48G 4SFP Switch (JL260A)

|                                   |   |  |
|-----------------------------------|---|--|
| <b>I/O ports and slots</b>        | 48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only<br>4 SFP |  |
| <b>Additional ports and slots</b> | 1 dual-personality (RJ-45 or USB micro-B) serial console port   |  |
| <b>Physical characteristics</b>   | <b>Dimensions</b>   | 17.42(w) x 9.7(d) x 1.73(h) in (44.25 x 24.63 x 4.39 cm)<br>(1U height)                  |
|                                   | <b>Weight</b>   | 6.83 lb (3.10 kg)  |
| <b>Memory and processor</b>       | Dual Core ARM Cortex @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.875MB Egress, 4 GB eMMC  |  |
| <b>Performance</b>                | <b>1000 Mb Latency</b>  | < 3.8 µs (64-byte packets)   |
|                                   | <b>Throughput</b>   | up to 77.4 Mpps  |
|                                   | <b>Switching capacity</b>   | 104 Gbps   |
|                                   | <b>Routing table size</b>   | 2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP                     |
|                                   | <b>MAC address table size</b>   | 32768 entries  |
| <b>Environment</b>                | <b>Operating temperature</b>  | 32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet |
|                                   | <b>Operating relative humidity</b>  | 15% to 95% @ 104°F (40°C), noncondensing   |
|                                   | <b>Non-operating/Storage temperature</b>  | -40°F to 158°F (-40°C to 70°C); up to 15000 Feet   |

### Technical Specifications

|                                   |   |  |
|-----------------------------------|---|--|
|                                   | <b>Non-operating/Storage temperature</b>  | 15% to 95% @ 149°F (65°C), noncondensing |
| <b>Environment</b>                | <b>Acoustic</b>   | Power: 54.1 dB, Pressure: 40.2 dB        |
|                                   | <b>Airflow direction</b>  | Side-to-side                             |
| <b>Electrical characteristics</b> | <b>Maximum heat dissipation</b>   | 100.0 BTU/hr (105.5 kJ/hr)               |
|                                   | <b>Voltage</b>  | 100 - 127 / 200 - 240 VAC, rated         |
|                                   | <b>Current</b>  | 0.9/0.6 A                                |
|                                   | <b>Maximum power rating</b>   | 46.6 W                                   |
|                                   | <b>Idle power</b>   | 32.7 W                                   |
|                                   | <b>Frequency</b>  | 50/60 Hz                                 |
| <b>Electrical characteristics</b> | <b>Notes:</b><br><br>Idle power is the actual power consumption of the device with no ports connected.<br><br>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |  |
| <b>Safety</b>                     | UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1  |  |
| <b>Emissions</b>                  | EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438   |  |
| <b>Immunity</b>                   | <b>Generic</b>  | EN 55024:2010/CISPR 24                   |
|                                   | <b>ESD</b>  | IEC 61000-4-2:                           |
|                                   | <b>Radiated</b>   | IEC 61000-4-3                            |
|                                   | <b>EFT/Burst</b>  | IEC 61000-4-4                            |
|                                   | <b>Surge</b>  | IEC 61000-4-5                            |
| <b>Immunity</b>                   | <b>Conducted</b>  | IEC 61000-4-6                            |
|                                   | <b>Power frequency magnetic field</b>   | IEC 61000-4-8                            |
|                                   | <b>Voltage dips and interruptions</b>   | IEC 61000-4-11                           |
|                                   | <b>Harmonics</b>  | IEC/EN 61000-3-2                         |
|                                   | <b>Flicker</b>  | IEC/EN 61000-3-3                         |
| <b>Management</b>                 | HPE Aruba Networking Central; HPE Aruba Networking Management Software (AirWave); IMC - Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP  |  |
| <b>Services</b>                   | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.            |  |

### HPE Aruba Networking 2930F 24G PoE+ 4SFP Switch (JL261A, JL261ACM) <sup>1</sup>

|                                   |   |
|-----------------------------------|---|
| <b>I/O ports and slots</b>        | 24 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only<br>4 SFP |
| <b>Additional ports and slots</b> | 1 dual-personality (RJ-45 or USB micro-B) serial console port   |

### Technical Specifications

|                                   |   |  |
|-----------------------------------|---|--|
| <b>Physical characteristics</b>   | <b>Dimensions</b>   | 17.42(w) x 11.98(d) x 1.73(h) in (44.25 x 30.42 x 4.39 cm) (1U height)                   |
|                                   | <b>Weight</b>   | 8.6 lb (3.9 kg)  |
| <b>Memory and processor</b>       | Dual Core ARM Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB<br>4.5MB Ingress/7.785 Egress, 4 GB eMMC  |  |
| <b>Performance</b>                | <b>1000 Mb Latency</b>  | < 3.8 µs (64-byte packets)   |
|                                   | <b>Throughput</b>   | up to 41.7 Mpps  |
|                                   | <b>Switching capacity</b>   | 56 Gbps  |
|                                   | <b>Routing table size</b>   | 2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP                     |
|                                   | <b>MAC address table size</b>   | 32768 entries  |
| <b>Environment</b>                | <b>Operating temperature</b>  | 32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet |
|                                   | <b>Operating relative humidity</b>  | 15% to 95% @ 104°F (40°C), noncondensing   |
|                                   | <b>Non-operating/Storage temperature</b>  | -40°F to 158°F (-40°C to 70°C); up to 15000 Feet   |
|                                   | <b>Non-operating/Storage temperature</b>  | 15% to 95% @ 149°F (65°C)  |
|                                   | <b>Acoustic</b>   | Power: 54.1 dB, Pressure: 40.6 dB  |
| <b>Electrical characteristics</b> | <b>Airflow direction</b>  | Side-to-side   |
|                                   | <b>Power efficiency certifications</b>  | 80plus.org certification: Silver   |
|                                   | <b>Maximum heat dissipation</b>   | 258.0 BTU/hr (272.2 kJ/hr)   |
|                                   | <b>Voltage</b>  | 100 - 127 / 200 - 240 VAC, rated   |
|                                   | <b>Current</b>  | 4.9/2.4 A  |
|                                   | <b>Maximum power rating</b>   | 445 W  |
|                                   | <b>Idle power</b>   | 36.8 W   |
|                                   | <b>PoE power</b>  | 370 W PoE+   |
| <b>Notes:</b>                     | <b>Frequency</b>  | 50/60 Hz   |
|                                   | <p>Idle power is the actual power consumption of the device with no ports connected.</p> <p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p> |  |
| <b>Safety</b>                     | UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1  |  |
| <b>Emissions</b>                  | EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438   |  |
| <b>Immunity</b>                   | <b>Generic</b>  | EN 55024:2010/CISPR 24   |
|                                   | <b>ESD</b>  | IEC 61000-4-2:   |
|                                   | <b>Radiated</b>   | IEC 61000-4-3  |
|                                   | <b>EFT/Burst</b>  | IEC 61000-4-4  |
|                                   | <b>Surge</b>  | IEC 61000-4-5  |
|                                   | <b>Conducted</b>  | IEC 61000-4-6  |
|                                   | <b>Power frequency magnetic field</b>   | IEC 61000-4-8  |

### Technical Specifications

|                   |  |                  |
|-------------------|--|------------------|
|                   | <b>Voltage dips and interruptions</b>  | IEC 61000-4-11   |
|                   | <b>Harmonics</b>   | IEC/EN 61000-3-2 |
|                   | <b>Flicker</b>   | IEC/EN 61000-3-3 |
| <b>Management</b> | HPE Aruba Networking Central; HPE Aruba Networking Management Software (AirWave); IMC - Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP   |                  |
| <b>Services</b>   | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.   |                  |
| <b>Notes:</b>     | <p><b>1</b> All hardware SKUs can be managed by HPE Aruba Networking Central. Central Managed (CM) SKUs are used for simplified ordering within U.S. and Canada only. Append "CM" to the indicated SKU #: (e.g., JL261ACM to order the JL261A). Requires an active Central license and end-user information consistent with the Central license purchase. Applicable accessories with a valid "CM" suffix should also be placed on the same order.</p> |                  |

### HPE Aruba Networking 2930F 48G PoE+ 4SFP Switch (JL262A, JL262ACM) **1**

|                                   |   |  |
|-----------------------------------|---|--|
| <b>I/O ports and slots</b>        | 48 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only<br>4 SFP |  |
| <b>Additional ports and slots</b> | 1 dual-personality (RJ-45 or USB micro-B) serial console port   |  |
| <b>Physical characteristics</b>   | <b>Dimensions</b>   | 17.42(w) x 11.98(d) x 1.73(h) in (44.25 x 30.42 x 4.39 cm) (1U height)                   |
|                                   | <b>Weight</b>   | 9.83 lb (4.46 kg)  |
| <b>Memory and processor</b>       | Dual Core ARM Cortex @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.875MB Egress, 4 GB eMMC  |  |
| <b>Performance</b>                | <b>1000 Mb Latency</b>  | < 3.8 µs (64-byte packets)   |
|                                   | <b>Throughput</b>   | up to 77.4 Mpps  |
|                                   | <b>Switching capacity</b>   | 104 Gbps   |
|                                   | <b>Routing table size</b>   | 2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP                     |
|                                   | <b>MAC address table size</b>   | 32768 entries  |
| <b>Environment</b>                | <b>Operating temperature</b>  | 32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet |
|                                   | <b>Operating relative humidity</b>  | 15% to 95% @ 104°F (40°C), noncondensing   |
|                                   | <b>Non-operating/Storage temperature</b>  | -40°F to 158°F (-40°C to 70°C); up to 15000 Feet   |
|                                   | <b>Non-operating/Storage temperature</b>  | 15% to 95% @ 149°F (65°C)  |
|                                   | <b>Acoustic</b>   | Power: 55.7 dB, Pressure: 41.7 dB  |
|                                   | <b>Airflow direction</b>  | Side-to-side   |
| <b>Electrical characteristics</b> | <b>Power efficiency certifications</b>  | 80plus.org certification: Silver   |
|                                   | <b>Maximum heat dissipation</b>   | 293.0 BTU/hr (309.1 kJ/hr)   |
|                                   | <b>Voltage</b>  | 100 - 127 / 200 - 240 VAC, rated   |

### Technical Specifications

|                             |  |                        |
|-----------------------------|--|------------------------|
| <b>Current</b>              | 5.1/2.5 A  |                        |
| <b>Maximum power rating</b> | 459 W  |                        |
| <b>Idle power</b>           | 48.6 W   |                        |
| <b>PoE power</b>            | 370 W PoE+   |                        |
| <b>Frequency</b>            | 50/60 Hz   |                        |
| <b>Notes:</b>               | <p>Idle power is the actual power consumption of the device with no ports connected.</p> <p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p>  |                        |
| <b>Safety</b>               | UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1   |                        |
| <b>Emissions</b>            | EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438  |                        |
| <b>Immunity</b>             | <b>Generic</b>   | EN 55024:2010/CISPR 24 |
|                             | <b>ESD</b>   | IEC 61000-4-2          |
|                             | <b>Radiated</b>  | IEC 61000-4-3          |
|                             | <b>EFT/Burst</b>   | IEC 61000-4-4          |
|                             | <b>Surge</b>   | IEC 61000-4-5          |
|                             | <b>Conducted</b>   | IEC 61000-4-6          |
|                             | <b>Power frequency magnetic field</b>  | IEC 61000-4-8          |
| <b>Immunity</b>             | <b>Voltage dips and interruptions</b>  | IEC 61000-4-11         |
|                             | <b>Harmonics</b>   | IEC/EN 61000-3-2       |
|                             | <b>Flicker</b>   | IEC/EN 61000-3-3       |
| <b>Management</b>           | HPE Aruba Networking Central; HPE Aruba Networking Management Software (AirWave); IMC - Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP   |                        |
| <b>Services</b>             | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.   |                        |
| <b>Notes:</b>               | <p><sup>1</sup> All hardware SKUs can be managed by HPE Aruba Networking Central. Central Managed (CM) SKUs are used for simplified ordering within U.S. and Canada only. Append "CM" to the indicated SKU #: (e.g., JL261ACM to order the JL261A). Requires an active Central license and end-user information consistent with the Central license purchase. Applicable accessories with a valid "CM" suffix should also be placed on the same order.</p> |                        |

### HPE Aruba Networking 2930F 24G PoE+ 4SFP+ TAA-compliant Switch (JL263A)

|                            |   |
|----------------------------|---|
| <b>I/O ports and slots</b> | 24 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100Basetx, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only<br>4 SFP+ 1/10GbE ports<br>PHY-less |
|----------------------------|---|

### Technical Specifications

|                                   |  |   |
|-----------------------------------|--|---|
| <b>Additional ports and slots</b> | 1 dual-personality (RJ-45 or USB micro-B) serial console port  |   |
| <b>Physical characteristics</b>   | <b>Dimensions</b>  | 17.42(w) x 11.98(d) x 1.73(h) in. (44.25 x 30.42 x 4.39 cm) (1U height)                     |
|                                   | <b>Weight</b>  | 8.6 lb (3.9 kg)   |
| <b>Memory and processor</b>       | Dual Core ARM® Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB<br>4.5 MB Ingress/7.785 MB Egress, 4 GB eMMC  |   |
| <b>Performance</b>                | <b>1000 Mb Latency</b>   | < 3.8 µs (64-byte packets)  |
|                                   | <b>10 Gbps Latency</b>   | < 2.9 µs (64-byte packets)  |
|                                   | <b>Throughput</b>  | Up to 95.2 Mpps   |
|                                   | <b>Switching capacity</b>  | 128 Gbps  |
|                                   | <b>Routing table size</b>  | 2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP                        |
|                                   | <b>MAC address table size</b>  | 32,768 entries  |
| <b>Environment</b>                | <b>Operating temperature</b>   | 32°F to 113°F (0°C to 45°C); up to 5000 Feet, -0°C to 40°C (32°F to 104°F) up to 10000 Feet |
|                                   | <b>Operating relative humidity</b>   | 15% to 95% @ 104°F (40°C), noncondensing  |
|                                   | <b>Non-operating/Storage temperature</b>   | -40°F to 158°F (-40°C to 70°C); up to 15000 Feet  |
|                                   | <b>Non-operating/Storage temperature</b>   | 15% to 95% @ 149°F (65°C)   |
|                                   | <b>Acoustic</b>  | Power: 54.1 dB, Pressure: 40.6 dB   |
|                                   | <b>Airflow direction</b>   | Side-to-side  |
| <b>Electrical characteristics</b> | <b>Power efficiency certifications</b>   | 80plus.org certification: Silver  |
|                                   | <b>Maximum heat dissipation</b>  | 258.0 BTU/hr (272.2kJ/hr)   |
|                                   | <b>Voltage</b>   | 100-127 / 200-240 VAC, rated  |
|                                   | <b>Current</b>   | 4.9/2.4 A   |
|                                   | <b>Maximum power rating</b>  | 445 W   |
|                                   | <b>Idle power</b>  | 36.8 W  |
|                                   | <b>PoE power</b>   | 370 W PoE+  |
|                                   | <b>Frequency</b>   | 50/60 Hz  |
| <b>Electrical characteristics</b> | <p><b>Notes:</b></p> <p>Idle power is the actual power consumption of the device with no ports connected.</p> <p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p> |   |
| <b>Safety</b>                     | UL 60950-1: 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1   |   |
| <b>Emissions</b>                  | EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438  |   |
| <b>Immunity</b>                   | <b>Generic</b>   | EN 55024:2010/CISPR 24  |
|                                   | <b>ESD</b>   | IEC 61000-4-2   |
|                                   | <b>Radiated</b>  | IEC 61000-4-3   |
|                                   | <b>EFT/Burst</b>   | IEC 61000-4-4   |

### Technical Specifications

|                                       |  |
|---------------------------------------|--|
| <b>Surge</b>                          | IEC 61000-4-5  |
| <b>Conducted</b>                      | IEC 61000-4-6  |
| <b>Power frequency magnetic field</b> | IEC 61000-4-8  |
| <b>Voltage dips and interruptions</b> | IEC 61000-4-11   |
| <b>Harmonics</b>                      | IEC/EN 61000-3-2   |
| <b>Flicker</b>                        | IEC/EN 61000-3-3   |
| <b>Management</b>                     | HPE Aruba Networking Central; HPE Aruba Networking Management Software (AirWave); IMC - Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP   |
| <b>Services</b>                       | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office. |

### HPE Aruba Networking 2930F 48G PoE+ 4SFP+ TAA-compliant Switch (JL264A)

|                                   |   |   |
|-----------------------------------|---|---|
| <b>I/O ports and slots</b>        | 48 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100Basetx, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only<br>4 SFP+ 1/10GbE ports<br>PHY-less |   |
| <b>Additional ports and slots</b> | 1 dual-personality (RJ-45 or USB micro-B) serial console port   |   |
| <b>Physical characteristics</b>   | <b>Dimensions</b>   | 17.42(w) x 11.98(d) x 1.73(h) in. (44.25 x 30.42 x 4.39 cm) (1U height)                     |
|                                   | <b>Weight</b>   | 9.83 lb (4.46 kg)   |
| <b>Memory and processor</b>       | Dual Core ARM® Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB<br>4.5 MB Ingress/7.785 MB Egress, 4 GB eMMC   |   |
| <b>Performance</b>                | <b>1000 Mb Latency</b>  | < 3.8 µs (64-byte packets)  |
|                                   | <b>10 Gbps Latency</b>  | < 2.9 µs (64-byte packets)  |
|                                   | <b>Throughput</b>   | Up to 112.0 Mpps  |
|                                   | <b>Switching capacity</b>   | 176 Gbps  |
|                                   | <b>Routing table size</b>   | 2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP                        |
|                                   | <b>MAC address table size</b>   | 32,768 entries  |
| <b>Environment</b>                | <b>Operating temperature</b>  | 32°F to 113°F (0°C to 45°C); up to 5000 Feet, -0°C to 40°C (32°F to 104°F) up to 10000 Feet |
|                                   | <b>Operating relative humidity</b>  | 15% to 95% @ 104°F (40°C), noncondensing  |
|                                   | <b>Non-operating/Storage temperature</b>  | -40°F to 158°F (-40°C to 70°C); up to 15000 Feet  |
|                                   | <b>Non-operating/Storage temperature</b>  | 15% to 95% @ 149°F (65°C)   |
| <b>Environment</b>                | <b>Acoustic</b>   | Power: 55.7 dB, Pressure: 41.7 dB   |
|                                   | <b>Airflow direction</b>  | Side-to-side  |
| <b>Electrical characteristics</b> | <b>Power efficiency certifications</b>  | 80plus.org certification: Silver  |
|                                   | <b>Maximum heat dissipation</b>   | 293.0 BTU/hr (309.1 kJ/hr)  |

### Technical Specifications

|                             |  |
|-----------------------------|--|
| <b>Voltage</b>              | 100-127 / 200-240 VAC, rated   |
| <b>Current</b>              | 5.1/2.5 A  |
| <b>Maximum power rating</b> | 459 W  |
| <b>Idle power</b>           | 48.6 W   |
| <b>PoE power</b>            | 370 W PoE+   |
| <b>Frequency</b>            | 50/60 Hz   |
| <b>Notes:</b>               | <p>Idle power is the actual power consumption of the device with no ports connected.</p> <p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p>    |
| <b>Safety</b>               | UL 60950-1: 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1   |
| <b>Emissions</b>            | EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438  |
| <b>Immunity</b>             | <b>Generic</b> EN 55024:2010/CISPR 24  |
|                             | <b>ESD</b> IEC 61000-4-2   |
|                             | <b>Radiated</b> IEC 61000-4-3  |
|                             | <b>EFT/Burst</b> IEC 61000-4-4   |
|                             | <b>Surge</b> IEC 61000-4-5   |
| <b>Immunity</b>             | <b>Conducted</b> IEC 61000-4-6   |
|                             | <b>Power frequency magnetic field</b> IEC 61000-4-8  |
|                             | <b>Voltage dips and interruptions</b> IEC 61000-4-11   |
|                             | <b>Harmonics</b> IEC/EN 61000-3-2  |
|                             | <b>Flicker</b> IEC/EN 61000-3-3  |
| <b>Management</b>           | HPE Aruba Networking Central; HPE Aruba Networking Management Software (AirWave); IMC - Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP   |
| <b>Services</b>             | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office. |

### HPE Aruba Networking 2930F 48G PoE+ 4SFP 740W Switch (JL557A)

|                                   |  |   |
|-----------------------------------|--|---|
| <b>I/O ports and slots</b>        | 48 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only<br>4 SFP+ |   |
| <b>Additional ports and slots</b> | 1 dual-personality (RJ-45 or USB micro-B) serial console port  |   |
| <b>Physical characteristics</b>   | <b>Dimensions</b>  | 17.42 (w) x 12.77 (d) x 1.73 (h) in<br>(44.25 x 32.42 x 4.39 cm)<br>(1U height) |
|                                   | <b>Weight</b>  | 10.56 lb (4.79 kg)  |

### Technical Specifications

|                                   |  |   |
|-----------------------------------|--|---|
| <b>Memory and processor</b>       | Dual Core ARM Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB<br>4.5MB Ingress/7.785 Egress, 4 GB eMMC   |   |
| <b>Performance</b>                | <b>1000 Mb Latency</b>   | < 3.8 µs (64-byte packets)  |
|                                   | <b>Throughput</b>  | up to 77.4 Mpps   |
|                                   | <b>Switching capacity</b>  | 104 Gbps  |
| <b>Performance</b>                | <b>Routing table size</b>  | 2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP                                  |
|                                   | <b>MAC address table size</b>  | 32,768  |
| <b>Environment</b>                | <b>Operating temperature</b>   | 32°F to 113°F (0°C to 45°C);<br>up to 5,000 Feet,<br>0°C to 40°C (32°F to 104°F)<br>up to 10,000 Feet |
|                                   | <b>Operating relative humidity</b>   | 15% to 95% @ 104°F (40°C), noncondensing  |
|                                   | <b>Non-operating/Storage temperature</b>   | -40°F to 158°F (-40°C to 70°C); up to 15,000 Feet   |
|                                   | <b>Non-operating/Storage temperature</b>   | 15% to 95% @ 149°F (65°C)   |
|                                   | <b>Acoustic (power and pressure) in decibels</b>   | Power: 55.1 dB, Pressure: 41.1 dB   |
|                                   | <b>Airflow direction</b>   | Side to side  |
| <b>Electrical characteristics</b> | <b>Power efficiency certifications</b>   | 80plus.org certification: Gold  |
|                                   | <b>Maximum heat dissipation</b>  | 420.9 BTU/hr (444.1 kJ/hr)  |
|                                   | <b>Voltage</b>   | 100-127 / 200-240 VAC, rated  |
|                                   | <b>Current</b>   | 9.2 / 4.9 A   |
|                                   | <b>Maximum power rating</b>  | 980W  |
|                                   | <b>Idle power</b>  | 49.9W   |
|                                   | <b>PoE power</b>   | 740 W PoE+  |
| <b>Frequency</b>                  | 50/60 Hz   |   |
| <b>Electrical characteristics</b> | <p><b>Notes:</b></p> <p>Idle power is the actual power consumption of the device with no ports connected.</p> <p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p> |   |
| <b>Safety</b>                     | UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1   |   |
| <b>Emissions</b>                  | EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438  |   |
| <b>Immunity</b>                   | <b>Generic</b>   | EN 55024:2010/CISPR 24  |
|                                   | <b>ESD</b>   | IEC 61000-4-2   |
|                                   | <b>Radiated</b>  | IEC 61000-4-3   |
|                                   | <b>EFT/Burst</b>   | IEC 61000-4-4   |
|                                   | <b>Surge</b>   | IEC 61000-4-5   |
|                                   | <b>Conducted</b>   | IEC 61000-4-6   |
|                                   | <b>Power frequency magnetic field</b>  | IEC 61000-4-8   |

### Technical Specifications

|                   |  |                  |
|-------------------|--|------------------|
|                   | <b>Voltage dips and interruptions</b>  | IEC 61000-4-11   |
|                   | <b>Harmonics</b>   | IEC/EN 61000-3-2 |
|                   | <b>Flicker</b>   | IEC/EN 61000-3-3 |
| <b>Management</b> | HPE Aruba Networking Central; HPE Aruba Networking Management Software (AirWave); IMC - Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP   |                  |
| <b>Services</b>   | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office. |                  |

### HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W Switch (JL558A, JL558ACM) 1

|                                   |  |   |
|-----------------------------------|--|---|
| <b>I/O ports and slots</b>        | 48 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only<br>4 SFP+ 1/10GbE ports<br>PHY-less |   |
| <b>Additional ports and slots</b> | 1 dual-personality (RJ-45 or USB micro-B) serial console port  |   |
| <b>Physical characteristics</b>   | <b>Dimensions</b>  | 17.42 (w) x 12.77 (d) x 1.73 (h) in<br>(44.25 x 32.42 x 4.39 cm)<br>(1U height)                       |
|                                   | <b>Weight</b>  | 10.56 lb (4.79 kg)  |
| <b>Memory and processor</b>       | Dual Core ARM Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB<br>4.5MB Ingress/7.785 Egress,4 GB eMMC  |   |
| <b>Performance</b>                | <b>1000 Mb Latency</b>   | < 3.8 µs (64-byte packets)  |
|                                   | <b>10Gbps latency</b>  | < 1.6 µs (64-byte packets)  |
|                                   | <b>Throughput</b>  | up to 112.0 Mpps  |
|                                   | <b>Switching capacity</b>  | 176 Gbps  |
|                                   | <b>Routing table size</b>  | 2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP                                  |
|                                   | <b>MAC address table size</b>  | 32,768  |
| <b>Environment</b>                | <b>Operating temperature</b>   | 32°F to 113°F (0°C to 45°C);<br>up to 5,000 Feet,<br>0°C to 40°C (32°F to 104°F)<br>up to 10,000 Feet |
|                                   | <b>Operating relative humidity</b>   | 15% to 95% @ 104°F (40°C), noncondensing  |
| <b>Environment</b>                | <b>Non-operating/Storage temperature</b>   | -40°F to 158°F (-40°C to 70°C); up to 15,000 Feet   |
|                                   | <b>Non-operating/Storage temperature</b>   | 15% to 95% @ 149°F (65°C)   |
|                                   | <b>Acoustic (power and pressure) in decibels</b>   | Power: 55.1 dB, Pressure: 41.1 dB   |
|                                   | <b>Airflow direction</b>   | Side to side  |
| <b>Electrical characteristics</b> | <b>Power efficiency certifications</b>   | 80plus.org certification: Gold  |
|                                   | <b>Maximum heat dissipation</b>  | 420.9 BTU/hr (444.1 kJ/hr)  |

### Technical Specifications

|                                       |   |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
|---------------------------------------|---|----------------|------------------------|------------|---------------|-----------------|---------------|------------------|---------------|--------------|---------------|------------------|---------------|---------------------------------------|---------------|---------------------------------------|----------------|------------------|------------------|----------------|------------------|
| <b>Voltage</b>                        | 100-127 / 200-240 VAC, rated  |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
| <b>Current</b>                        | 9.2 / 4.9 A   |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
| <b>Maximum power rating</b>           | 980W  |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
| <b>Idle power</b>                     | 49.9W   |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
| <b>PoE power</b>                      | 740 W PoE+  |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
| <b>Frequency</b>                      | 50/60 Hz  |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
| <b>Notes:</b>                         | <p>Idle power is the actual power consumption of the device with no ports connected.</p> <p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p>   |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
| <b>Safety</b>                         | UL 60950-1, 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1  |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
| <b>Emissions</b>                      | EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438   |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
| <b>Immunity</b>                       | <table border="1"><tr><td><b>Generic</b></td><td>EN 55024:2010/CISPR 24</td></tr><tr><td><b>ESD</b></td><td>IEC 61000-4-2</td></tr><tr><td><b>Radiated</b></td><td>IEC 61000-4-3</td></tr><tr><td><b>EFT/Burst</b></td><td>IEC 61000-4-4</td></tr><tr><td><b>Surge</b></td><td>IEC 61000-4-5</td></tr><tr><td><b>Conducted</b></td><td>IEC 61000-4-6</td></tr><tr><td><b>Power frequency magnetic field</b></td><td>IEC 61000-4-8</td></tr><tr><td><b>Voltage dips and interruptions</b></td><td>IEC 61000-4-11</td></tr><tr><td><b>Harmonics</b></td><td>IEC/EN 61000-3-2</td></tr><tr><td><b>Flicker</b></td><td>IEC/EN 61000-3-3</td></tr></table> | <b>Generic</b> | EN 55024:2010/CISPR 24 | <b>ESD</b> | IEC 61000-4-2 | <b>Radiated</b> | IEC 61000-4-3 | <b>EFT/Burst</b> | IEC 61000-4-4 | <b>Surge</b> | IEC 61000-4-5 | <b>Conducted</b> | IEC 61000-4-6 | <b>Power frequency magnetic field</b> | IEC 61000-4-8 | <b>Voltage dips and interruptions</b> | IEC 61000-4-11 | <b>Harmonics</b> | IEC/EN 61000-3-2 | <b>Flicker</b> | IEC/EN 61000-3-3 |
| <b>Generic</b>                        | EN 55024:2010/CISPR 24  |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
| <b>ESD</b>                            | IEC 61000-4-2   |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
| <b>Radiated</b>                       | IEC 61000-4-3   |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
| <b>EFT/Burst</b>                      | IEC 61000-4-4   |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
| <b>Surge</b>                          | IEC 61000-4-5   |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
| <b>Conducted</b>                      | IEC 61000-4-6   |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
| <b>Power frequency magnetic field</b> | IEC 61000-4-8   |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
| <b>Voltage dips and interruptions</b> | IEC 61000-4-11  |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
| <b>Harmonics</b>                      | IEC/EN 61000-3-2  |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
| <b>Flicker</b>                        | IEC/EN 61000-3-3  |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
| <b>Management</b>                     | HPE Aruba Networking Central; HPE Aruba Networking Management Software (AirWave); IMC - Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP  |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
| <b>Services</b>                       | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.  |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |
| <b>Notes:</b>                         | <p><sup>1</sup> All hardware SKUs can be managed by HPE Aruba Networking Central. Central Managed (CM) SKUs are used for simplified ordering within U.S. and Canada only. Append "CM" to the indicated SKU #: (e.g., JL261ACM to order the JL261A). Requires an active Central license and end-user information consistent with the Central license purchase. Applicable accessories with a valid "CM" suffix should also be placed on the same order.</p>  |                |                        |            |               |                 |               |                  |               |              |               |                  |               |                                       |               |                                       |                |                  |                  |                |                  |

### HPE Aruba Networking 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch (JL559A)

|                            |  |
|----------------------------|--|
| <b>I/O ports and slots</b> | 48 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only<br>4 SFP+ 1/10GbE ports<br>PHY-less |
|----------------------------|--|

### Technical Specifications

|   |  |   |
|---|--|---|
| <b>Additional ports and slots</b>   | 1 dual-personality (RJ-45 or USB micro-B) serial console port  |   |
| <b>Physical characteristics</b>   | <b>Dimensions</b>  | 17.42 (w) x 12.77 (d) x 1.73 (h) in<br>(44.25 x 32.42 x 4.39 cm)<br>(1U height)                       |
|   | <b>Weight</b>  | 10.56 lb (4.79 kg)  |
| <b>Memory and processor</b>   | Dual Core ARM Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB<br>4.5MB Ingress/7.785 Egress, 4 GB eMMC   |   |
| <b>Performance</b>  | <b>1000 Mb Latency</b>   | < 3.8 µs (64-byte packets)  |
|   | <b>10Gbps latency</b>  | < 1.6 µs (64-byte packets)  |
|   | <b>Throughput</b>  | up to 112.0 Mpps  |
|   | <b>Switching capacity</b>  | 176 Gbps  |
|   | <b>Routing table size</b>  | 2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP                                  |
|   | <b>MAC address table size</b>  | 32,768  |
| <b>Environment</b>  | <b>Operating temperature</b>   | 32°F to 113°F (0°C to 45°C);<br>up to 5,000 Feet,<br>0°C to 40°C (32°F to 104°F)<br>up to 10,000 Feet |
|   | <b>Operating relative humidity</b>   | 15% to 95% @ 104°F (40°C), noncondensing  |
|   | <b>Non-operating/Storage temperature</b>   | -40°F to 158°F (-40°C to 70°C); up to 15,000 Feet   |
|   | <b>Non-operating/Storage temperature</b>   | 15% to 95% @ 149°F (65°C)   |
|   | <b>Acoustic (power and pressure) in decibels</b>   | Power: 55.1 dB, Pressure: 41.1 dB   |
| <b>Environment</b>  | <b>Airflow direction</b>   | Side to side  |
| <b>Electrical characteristics</b>   | <b>Power efficiency certifications</b>   | 80plus.org certification: Gold  |
|   | <b>Maximum heat dissipation</b>  | 420.9 BTU/hr (444.1 kJ/hr)  |
|   | <b>Voltage</b>   | 100-127 / 200-240 VAC, rated  |
|   | <b>Current</b>   | 9.2 / 4.9 A   |
|   | <b>Maximum power rating</b>  | 980W  |
|   | <b>Idle power</b>  | 49.9W   |
|   | <b>PoE power</b>   | 740 W PoE+  |
|   | <b>Frequency</b>   | 50/60 Hz  |
| <b>Notes:</b>   |  |   |
| Idle power is the actual power consumption of the device with no ports connected.   |  |   |
| Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |  |   |
| <b>Safety</b>   | UL 60950-1: 2nd Edition; UL 62368-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; EN 62368-1: 2nd Edition; CSA 22.2 No. 60950-1-07 2nd; IEC-62368-1: 2nd Edition; EN 60825-1:2014 / IEC 60825-1:2014 Class 1 |   |
| <b>Emissions</b>  | EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438  |   |
| <b>Immunity</b>   | <b>Generic</b>   | EN 55024:2010/CISPR 24  |

### Technical Specifications

|                                       |  |
|---------------------------------------|--|
| <b>ESD</b>                            | IEC 61000-4-2  |
| <b>Radiated</b>                       | IEC 61000-4-3  |
| <b>EFT/Burst</b>                      | IEC 61000-4-4  |
| <b>Surge</b>                          | IEC 61000-4-5  |
| <b>Conducted</b>                      | IEC 61000-4-6  |
| <b>Power frequency magnetic field</b> | IEC 61000-4-8  |
| <b>Voltage dips and interruptions</b> | IEC 61000-4-11   |
| <b>Harmonics</b>                      | IEC/EN 61000-3-2   |
| <b>Flicker</b>                        | IEC/EN 61000-3-3   |
| <b>Management</b>                     | HPE Aruba Networking Central; HPE Aruba Networking Management Software (AirWave); IMC - Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP   |
| <b>Services</b>                       | Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office. |

### Standards and Protocols

Applies to all products in series

#### Denial of service protection

CPU DoS Protection

#### Device Management

- RFC 1155 Structure and Mgmt Information (SMIv1)
- RFC 1157 SNMPv1/v2c
- RFC 1591 DNS (client)
- RFC 1901 (Community based SNMPv2)
- RFC 1901-1907 SNMPv2c, SMIv2 and Revised MIB-II
- RFC 1908 (SNMP v1/2 Coexistence)
- RFC 2576 (Coexistence between SNMP V1, V2, V3)
- RFC 2578-2580 SMIv2
- RFC 2579 (SMIv2 Text Conventions)
- RFC 2580 (SMIv2 Conformance)
- RFC 2819 (RMON groups Alarm, Event, History and Statistics only)
- RFC 3416 (SNMP Protocol Operations v2)
- RFC 3417 (SNMP Transport Mappings)
- HTML and telnet management
- HTTP, SSHv1, and Telnet
- Multiple Configuration Files
- Multiple Software Images
- SNMP v3 and RMON RFC support
- SSHv1/SShv2 Secure Shell
- TACACS/TACACS+
- Web UI

#### IP Multicast

- RFC 1112 IGMP
- RFC 2236 IGMPv2

### Technical Specifications

- RFC 2710 Multicast Listener Discovery (MLD) for IPv6
- RFC 3376 IGMPv3
- RFC 4541 Considerations for Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) Snooping Switches

### QoS/CoS

- IEEE 802.1p (CoS)
- RFC 2474 DiffServ Precedence, including 8 queues/port
- RFC 2475 DiffServ Architecture
- RFC 2597 DiffServ Assured Forwarding (AF)
- RFC 2598 DiffServ Expedited Forwarding (EF)
- Ingress Rate Limiting

### General Protocols

- IEEE 802.1AX-2008 Link Aggregation
- IEEE 802.1D MAC Bridges
- IEEE 802.1p Priority
- IEEE 802.1Q VLANs
- IEEE 802.1s Multiple Spanning Trees
- IEEE 802.1v VLAN classification by Protocol and Port
- IEEE 802.1w Rapid Reconfiguration of Spanning Tree
- IEEE 802.3ab 1000BASE-T
- IEEE 802.3ad Link Aggregation Control Protocol (LACP)
- IEEE 802.3af Power over Ethernet
- IEEE 802.3at PoE+
- IEEE 802.3az Energy Efficient Ethernet
- IEEE 802.3x Flow Control
- IEEE 802.1ad Q-in-Q
- RFC 768 UDP
- RFC 783 TFTP Protocol (revision 2)
- RFC 792 ICMP
- RFC 793 TCP
- RFC 826 ARP
- RFC 854 TELNET
- RFC 868 Time Protocol
- RFC 951 BOOTP
- RFC 1058 RIPv1
- RFC 1256 ICMP Router Discovery Protocol (IRDP)
- RFC 1350 TFTP Protocol (revision 2)
- RFC 1519 CIDR
- RFC 1542 BOOTP Extensions
- RFC 1918 Address Allocation for Private Internet
- RFC 2030 Simple Network Time Protocol (SNTP) v4
- RFC 2131 DHCP
- RFC 2236 IGMP Snooping
- RFC 2453 RIPv2
- RFC 2865 Remote Authentication Dial In User Service (RADIUS)
- RFC 2866 RADIUS Accounting
- RFC 3046 DHCP Relay Agent Information Option
- RFC 3411 An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks
- RFC 3412 Message Processing and Dispatching for the Simple Network Management Protocol (SNMP)
- RFC 3413 Simple Network Management Protocol (SNMP) Applications

### Technical Specifications

- RFC 3414 User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)
- RFC 3415 View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)
- RFC 3416 Protocol Operations for SNMP
- RFC 3417 Transport Mappings for the Simple Network Management Protocol (SNMP)
- RFC 3418 Management Information Base (MIB) for the Simple Network Management Protocol (SNMP)
- RFC 3575 IANA Considerations for RADIUS
- RFC 3576 Ext to RADIUS (CoA only)
- RFC 4541 Considerations for Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) Snooping Switches
- RFC 4675 RADIUS VLAN & Priority
- RFC 4861 Neighbor Discovery for IP version 6 (IPv6)
- RFC 4862 IPv6 Stateless Address Autoconfiguration
- RFC 5905 Network Time Protocol Version 4: Protocol and Algorithms Specification
- UDLD (Uni-directional Link Detection)

### IPv6

- RFC 1981 IPv6 Path MTU Discovery
- RFC 2080 RIPng for IPv6
- RFC 2081 RIPng Protocol Applicability Statement
- RFC 2082 RIP-2 MD5
- RFC 2460 IPv6 Specification
- RFC 2464 Transmission of IPv6 over Ethernet Networks
- RFC 2710 Multicast Listener Discovery (MLD) for IPv6
- RFC 2925 Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations (Ping only)
- RFC 2925 Remote Operations MIB (Ping only)
- RFC 3019 MLdv1 MIB
- RFC 3315 DHCPv6 (client and relay)
- RFC 3484 Default Address Selection for IPv6
- RFC 3513 IPv6 Addressing Architecture
- RFC 3596 DNS Extension for IPv6
- RFC 3810 MLdv2 for IPv6
- RFC 4022 MIB for TCP
- RFC 4113 MIB for UDP
- RFC 4251 SSHv6 Architecture
- RFC 4252 SSHv6 Authentication
- RFC 4253 SSHv6 Transport Layer
- RFC 4254 SSHv6 Connection
- RFC 4291 IP Version 6 Addressing Architecture
- RFC 4293 MIB for IP
- RFC 4419 Key Exchange for SSH
- RFC 4443 ICMPv6
- RFC 4541 IGMP & MLD Snooping Switch
- RFC 4861 IPv6 Neighbor Discovery
- RFC 4862 IPv6 Stateless Address Auto-configuration
- RFC 5095 Deprecation of Type 0 Routing Headers in IPv6
- RFC 6620 FCFS SAVI

### Summary of Changes

| Date        | Version History | Action  | Description of Change:  |
|-------------|-----------------|---------|---|
| 18-Nov-2024 | Version 31      | Changed | Overview, Standard Features Configuration Information and Technical specifications sections were updated.                             |
| 07-Oct-2024 | Version 30      | Changed | Standard Features and Configuration Information sections were updated.  |
| 22-Jan-2024 | Version 29      | Changed | Series name was updated.  |
| 20-Nov-2023 | Version 28      | Changed | Configuration Information section was updated. Obsolete SKUs were removed.  |
| 07-Aug-2023 | Version 27      | Changed | Configuration Information section was updated.  |
| 15-May-2023 | Version 26      | Changed | Configuration Information section was updated.  |
| 06-Feb-2023 | Version 25      | Changed | Configuration Information section was updated.  |
| 05-Dec-2022 | Version 24      | Changed | Configuration Information section was updated. Obsolete SKUs were removed and new SKUs were added.                                    |
| 07-Nov-2022 | Version 23      | Changed | Configuration Information section was updated. Obsolete SKUs were removed.  |
| 28-Jun-2021 | Version 22      | Changed | Standard Features and Configuration Information sections were updated. SKUs were added in Configuration Information section.          |
| 08-Mar-2021 | Version 21      | Changed | SKUs added in Configuration Information section.  |
| 21-Sep-2020 | Version 20      | Changed | Overview and Technical Specification sections were updated. New SKUs were added.  |
| 08-Sep-2020 | Version 19      | Changed | Configuration Information, Standard Features and Technical Specification sections were updated.                                       |
| 01-Jun-2020 | Version 18      | Changed | Standard Features and Technical Specification sections were updated.  |
| 06-Apr-2020 | Version 17      | Changed | Configuration Information section was updated. TAA transceivers were added, Obsolete SKUs were removed.                               |
| 02-Dec-2019 | Version 16      | Changed | Configuration Information section was updated. Obsolete SKUs were removed.  |
| 04-Nov-2019 | Version 15      | Changed | Overview, Standard Features, Configuration Information and Technical Specification sections were updated.                             |
| 07-Oct-2019 | Version 14      | Changed | Overview, Standard Features, Configuration Information and Technical Specification sections were updated.                             |
| 05-Aug-2019 | Version 13      | Changed | Configuration Information section was updated   |
| 01-Jul-2019 | Version 12      | Changed | Standard Features and Technical Specification sections were updated.<br>SKU descriptions were updated.<br>Obsolete SKUs were removed. |
| 04-Mar-2019 | Version 11      | Changed | SKU J9151D was replaced with J9151E<br>Obsolete SKUs were removed.  |
| 03-Dec-2018 | Version 10      | Changed | Software feature update: Key features, Product overview, Enhanced Capabilities and Technical Specifications updated                   |
| 02-Jul-2018 | Version 9       | Changed | Software feature update   |
| 15-Jan-2018 | Version 8       | Changed | Minor changes made on Technical Specifications  |
| 08-Jan-2018 | Version 7       | Added   | Models added: JL557A, JL558A, JL559A  |
| 03-Jul-2017 | Version 6       | Added   | SKU added: JL448A   |
| 20-Jan-2017 | Version 5       | Changed | Minor changes made on Standards and protocols   |
| 07-Nov-2016 | Version 4       | Changed | Product overview, Features and Benefits, Technical Specifications updated   |
| 02-Sep-2016 | Version 3       | Changed | Product description updated.  |
| 24-Jun-2016 | Version 2       | Changed | Updated B2E Attribute Description for all switches on the Configuration section.  |
| 06-Jun-2016 | Version 1       | New     | New QuickSpecs  |

### Summary of Changes

### Copyright

Make the right purchase decision. Contact our presales specialists.



---

© Copyright 2024 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

To learn more, visit: <http://www.hpe.com/networking>

c05052929 - 15576 - Worldwide - V31 - 18-November-2024

