



DELL EMC UNITY XT STORAGE SERIES

Simplify the path to IT transformation and unlock the full potential of your data capital with the new Dell EMC Unity XT storage arrays that feature up to 2X more IOPS, more memory, and up to 50% more drives than previous Dell EMC Unity models. These All-Flash and Hybrid storage systems with dual-active controller architecture and enterprise-class features are designed for performance, optimized for efficiency with up to 5:1 data reduction, and built to simplify your multi-cloud journey.

Architecture

Based on the powerful family of Intel Xeon™ processors, Dell EMC's Unity XT storage systems implement an integrated architecture for block, file, and VMware VVols with concurrent support for native NAS, iSCSI, and Fibre Channel protocols. Each system leverages dual storage processors, full 12 Gb SAS back end connectivity and Dell EMC's patented multicore architected operating environment to deliver unparalleled performance & efficiency. Additional storage capacity is added via Disk Array Enclosures (DAEs).

Physical Specifications

| | 380F/380 | 480F/480 | 680F/680 | 880F/880 |
|--|--|--|--|---|
| Min/Max Drives | 6/500 | 6/750 | 6/1000 | 6/1500 |
| Array Enclosure | A 2U Disk Processor Enclosure (DPE) with twenty five 2.5" drives | | | |
| Drive Enclosure (DAE - Disk Array Enclosure) | All-Flash (F) models support 2.5" drives in 2U twenty five drive and 3U eighty drive trays. Hybrid models support 2.5" drives in 2U twenty five drive and 3U eighty drive trays; and 3.5" drives in 3U fifteen drive trays. | | | |
| Standby Power System | Dell EMC Unity systems are powered by 2 power supplies (PS) per DPE/DAE. Each power supply can provide power to the entire module if the peer PS has been removed or is faulted. DPE power during a power failure is provided by a Battery Back Up (BBU) module. BBU is located within the SP enclosure and provides power to a single module (power zone) | | | |
| RAID Options | 1/0, 5, 6 | | | |
| CPU per Array | 2 x Intel CPUs, 12 cores per Array, 1.7GHz | 2 x dual-socket Intel CPUs, 32 cores per Array, 1.8GHz | 2 x dual-socket Intel CPUs, 48 cores per Array, 2.1GHz | 2 x dual-socket Intel CPUs 64 cores per Array, 2.1GHz |
| System Memory/Cache per Array | 128 GB | 192 GB | 384 GB | 768 GB |
| Max FAST Cache per Array* | Up to 800 GBs | Up to 1.2 TBs | Up to 3.2 TBs | Up to 6.0TBs |
| Total Cache ^A | Up to 928 GBs | Up to 1.39 TBs | Up to 3.58 TBs | Up to 6.76 TBs |
| Max Mezzanine cards per Array ^B | NA | 2 | 2 | 2 |
| Max IO Modules per Array ^C | 4 | 4 | 4 | 4 |
| Embedded SAS IO Ports per Array | 4 x 4 lane 12Gb/s SAS ports for BE (back end) Connection | 4 x 4 lane 12Gb/s SAS ports for BE Connection | 4 x 4 lane 12Gb/s SAS ports for BE Connection | 4 x 4 lane 12Gb/s SAS ports for BE Connection |

| | 380F/380 | 480F/480 | 680F/680 | 880F/880 |
|---|--|--|--|--|
| Optional SAS IO ports per Array | NA | 8 x 4 lane or 4 x 8 lane 12Gb/s SAS ports (for BE Connection) | 8 x 4 lane or 4 x 8 lane 12Gb/s SAS ports (for BE Connection) | 8 x 4 lane or 4 x 8 lane 12Gb/s SAS ports (for BE Connection) |
| Base 12 Gb/s SAS BE Buses per Array | 2 x 4 Lane | 2 x 4 Lane | 2 x 4 Lane | 2 x 4 Lane |
| Max 12 Gb/s SAS BE Buses per Array | 2 x 4 Lane | 6 x 4 Lane; or 2 x 4 lane and 2 x 8 lane | 6 x 4 Lane; or 2 x 4 lane and 2 x 8 lane | 6 x 4 Lane; or 2 x 4 lane and 2 x 8 lane |
| Max FE (front end) Total Ports per Array (all types) | 24 | 24 | 24 | 24 |
| Max Initiators per Array | 1,024 | 2,048 | 2,048 | 4,096 |
| Max FC Ports per Array | 20 | 16 | 16 | 16 |
| Embedded 10GbaseT Ports per Array | 4 | NA | NA | NA |
| Embedded CNA ports per Array | 4 ports: 8/16 Gb FC ^D , 10Gb IP/iSCSI, or 1Gb RJ45 | NA | NA | NA |
| 1 Gbase-T/iSCSI Max Total Ports per Array | 24 | 24 | 24 | 24 |
| 10/25 GbE/iSCSI Max Total Ports per Array | 24 – 10GbE 16 – 25GbE | 24 | 24 | 24 |
| Max Raw Capacity ^E | 2.4 PBs | 4.0 PBs | 8.0 PBs | 16.0 PBs |
| Max SAN Hosts | 512 | 1,024 | 1,024 | 2,048 |
| Max Number of Pools | 20 | 30 | 40 | 100 |
| Max Number of LUNs per Array | 1,000 | 1,500 | 2,000 | 6,000 |
| Max LUN Size | 256 TB | 256 TB | 256 TB | 256 TB |
| Max file systems per Array | 1000 | 1500 | 2000 | 4000 |
| Max File System Size | 256 TB | 256 TB | 256 TB | 256 TB |
| Max attached snapshots per Array (Block) | 1000 | 1500 | 2000 | 6000 |
| IOPS ^F (All Flash Models 380F – 880F) | up to 600K | up to 1.68M | up to 2.36M | up to 2.56M |
| OS Support | See the Dell EMC Simple Support Matrix on dell EMC.com | | | |
| ^A Specific to Hybrid Arrays ^B One Mezzanine card per Storage Processor (SP), mirrored. ^C Two IO Modules per Storage Processor (SP), mirrored. ^D 16Gb available in both single mode and multimode. ^E Maximum raw capacity will vary based on drive sizes available at time of purchase. ^F 100% sequential Reads, 4K block size, thick LUNs | | | | |

Connectivity

Connectivity options via Mezzanine cards and IO modules for both the file for NFS/SMB connectivity and the block storage for FC and iSCSI host connectivity (see above table for number of modules supported per SP).

| Connectivity Options | | |
|--|---|---|
| Type | Description | Details |
| Mezzanine card or IO Module | Four-Port 10Gbase-T Module (File & Block) | Four port 10Gbase-T Ethernet IP/iSCSI module with four 10Gbase-T Ethernet ports with copper connection to Ethernet switch |
| Mezzanine card or IO Module | Four-Port 10 Gb/s Optical Module (File & Block) | Four port 10GbE IP/iSCSI module with choice of SFP+ optical connection or active/passive twinax copper connection to Ethernet switch |
| Mezzanine card or IO Module | Four-Port 25 Gb/s Optical Module (File & Block) | Four port 10GbE IP/iSCSI module with choice of SFP+ optical connection or passive twinax copper connection to Ethernet switch |
| IO Module | Four-Port 16 Gb/s Fibre Channel Module (Block only) | Four port FC module with four ports auto-negotiating to 4/8/16 Gbps; uses single mode or multimode optical SFP and OM2/OM3/OM4 cabling to connect directly to host HBA or FC switch |
| IO Module | Four-Port 12 Gb/s SAS V3.0 Module* | Four port SAS module, used for back-end storage (DAE) connectivity to Storage Processors. Each SAS port has 4 lanes/port @ 12Gbps, delivering 48Gbps nominal throughput. Also available specifically for the 80 drive DAE is 8 lane connectivity utilizing a pair of SAS ports to deliver high bandwidth for added performance. |
| * For 480F/480, 680F/680 and 880F/880 models | | |

Maximum Cable Lengths

Shortwave optical OM4: 125 meters (16 Gb) 190 meters (8 Gb), 400 meters (4 Gb), and 500 meters (2 Gb)

Back-end (Drive) Connectivity

Each storage processor connects to one side of each of two redundant pairs of four-lane x 12 Gb/s Serial Attached SCSI (SAS) buses, providing continuous drive access to hosts in the event of a storage processor or bus fault. All models require four “system” drives and support a platform specific maximum number of disks (see Physical Specifications table above). 107 GBs per system drive on the Dell EMC Unity XT 380 models and 150 GBs on the Dell EMC Unity XT 480, 680, and 880 models is consumed by the operating environment software and data structures.

| Disk Array Enclosure (DAE) | | | |
|----------------------------|---------------------|---------------------|--|
| | 25 X 2.5" Drive DAE | 80 X 2.5" Drive DAE | 15 X 3.5" Drive DAE (Hybrid Arrays only) |
| Drive Types Supported | FLASH & SAS | FLASH & SAS | NL-SAS |
| Controller Interface | 12 Gb SAS | 12 Gb SAS | 12 Gb SAS |

| Supported Media | | | | | | | | | |
|-----------------|-----------|---------------|------------------|---------------------|-----------|--------------|---------------------|---------------------|---------------------|
| System Category | Type | Usage/Purpose | Nominal Capacity | Formatted Capacity* | Interface | DPE 25 Drive | 25 X 2.5" Drive DAE | 80 X 2.5" Drive DAE | 15 X 3.5" Drive DAE |
| All-Flash | SSD (SAS) | All-Flash | 800 GB | 733.5 GB | 12 Gb SAS | ✓ | ✓ | ✓ | |
| All-Flash | SSD (SAS) | All-Flash | 1.92 TB | 1751.9 GB | 12 Gb SAS | ✓ | ✓ | ✓ | |
| All-Flash | SSD (SAS) | All-Flash | 3.84 TB | 3503.9 GB | 12 Gb SAS | ✓ | ✓ | ✓ | |

| | | | | | | | | | |
|-----------|-------------------|-------------------------|----------|------------|-----------|---|---|---|---|
| All-Flash | SSD (SAS) | All-Flash | 7.68 TB | 7006.9 GB | 12 Gb SAS | ✓ | ✓ | ✓ | |
| All-Flash | SSD (SAS) | All-Flash | 15.36 TB | 14014.9 GB | 12 Gb SAS | ✓ | ✓ | ✓ | |
| Hybrid | SSD (SAS) | FAST Cache & Mixed Pool | 400 GB | 366.7 GB | 12 Gb SAS | ✓ | ✓ | ✓ | |
| Hybrid | SSD (SAS) | Mixed Pool | 800 GB | 733.5 GB | 12 Gb SAS | ✓ | ✓ | ✓ | |
| Hybrid | SSD (SAS) | Mixed Pool | 1.6 TB | 1467.45 GB | 12 Gb SAS | ✓ | ✓ | ✓ | |
| Hybrid | SSD (SAS) | Mixed Pool | 3.2 TB | 2919.9 GB | 12 Gb SAS | ✓ | ✓ | ✓ | |
| Hybrid | SSD (SAS) | All-Flash | 7.6 TB | 7006.9 GB | 12 Gb SAS | ✓ | ✓ | ✓ | |
| Hybrid | 10K HDD (SAS) | Mixed Pool | 600 GB | 536.7 GB | 12 Gb SAS | ✓ | ✓ | ✓ | |
| Hybrid | 10K HDD (SAS) | Mixed Pool | 1.2 TB | 1100.5 GB | 12 Gb SAS | ✓ | ✓ | ✓ | |
| Hybrid | 10K HDD (SAS) | Mixed Pool | 1.8 TB | 1650.8 GB | 12 Gb SAS | ✓ | ✓ | ✓ | |
| Hybrid | 7.2K HDD (NL-SAS) | Mixed Pool | 4.0 TB | 3668.6 TB | 12 Gb SAS | | | | ✓ |
| Hybrid | 7.2K HDD (NL-SAS) | Mixed Pool | 6.0 TB | 5505.0 TB | 12 Gb SAS | | | | ✓ |
| Hybrid | 7.2K HDD (NL-SAS) | Mixed Pool | 12.0 TB | 10948.7 TB | 12 Gb SAS | | | | ✓ |

*GB = Base2 GiB (GiB = 1024x1024x1024)

All drives are 520 bytes/sector.

All drives are non-SED. Data at Rest Encryption is done via the storage controller

Dell EMC Unity OE Protocols and Software Facilities

Support is provided for a wide variety of protocols and advanced features available via various software suites, plug-ins, drivers and packs.

| Protocols and Facilities Supported | | |
|---|---|--|
| Access-based Enumeration (ABE) for SMB protocol | Address Resolution Protocol (ARP) | Block Protocols: iSCSI, Fibre Channel (FCP SCSI-3) |
| Controller based Data at Rest Encryption (D@RE), with self-managed keys | DFS Distributed File System (Microsoft) as Leaf node or Standalone Root Server | Direct Host Attach for Fibre Channel and iSCSI |
| Dynamic Access Control (DAC) with claims support | Fail-Safe Networking (FSN) | Internet Control Message Protocol (ICMP) |
| Kerberos Authentication | Key Management Interoperability Protocol (KMIP) compliant external key manager for D@RE | LDAP (Lightweight Directory Access Protocol) |
| LDAP SSL | Link Aggregation for File (IEEE 802.3ad) | Lock Manager (NLM) v1, v2, v3, and v4 |
| Management & Data Ports IPv4 and/or IPv6 | NAS Servers Multi-protocol for UNIX and SMB clients (Microsoft, Apple, Samba) | Network Data Management Protocol (NDMP) v1-v4, 2-way & 3-way |
| Network Information Service (NIS) Client | Network Status Monitor (NSM) v1 Network Status Monitor (NSM) v1 | Network Time Protocol (NTP) client |
| NFS v3/v4 Secure Support | NT LAN Manager (NTLM) | Portmapper v2 |
| REST API: Open API that uses HTTP requests to provide management | Restriction of Hazardous Substances (RoHS) compliance | RSVD v1 for Microsoft Hyper-V |
| Simple Home Directory access for SMB protocol | SMI-S v1.6.0 compatible Dell EMC Unity Block & File client | Simple Mail Transfer Protocol (SMTP) |
| Simple Network Management Protocol v2c & v3 (SNMP) | Virtual LAN (IEEE 802.1q) | VMware Virtual Volumes (VVols) 2.0 |

Security & Compliance (applies to all Dell EMC Unity XT systems, except Dell EMC UnityVSA)

| |
|---|
| Common Criteria (in planning) |
| Controller based Data at Rest Encryption (D@RE) with self-managed keys |
| KMIP compliant external key manager for D@RE |
| FIPS 140-2 Level 1 validation (in planning) |
| IPv6 and dual stack (IPv4) modes of operation |
| Native SHA2 certificate |
| Security Technical Implementation Guide /Security Requirements Guide (STIG/SRG) |
| TLS 1.2 support and TLS 1.0 disablement |
| File-Level Retention: Enterprise FLR-E and Compliance FLR-C with requirements for SEC rule 17a-4(f) |

| Software | |
|---|---|
| All Inclusive Base Software | <p>Management Software:</p> <ul style="list-style-type: none"> • Unisphere: Element Manager • Unisphere Central: Consolidated dashboard and alerting • CloudIQ: Cloud-based storage analytics • Thin Provisioning • Dynamic Pools - All-Flash Arrays (AFA) only • Data Reduction: Zero Detect/Deduplication/Compression (AFA and All-Flash Pools in Hybrid Arrays, Block & File) • Proactive Assist: Configure remote support, online chat, open a service request, etc. • Quality of Service (Block and VVols) • Dell EMC Storage Analytics Adapter for VMware® vRealize™ • File & Block Tiering / Archiving to Public/Private Cloud (Cloud Tiering Appliance) • File-Level Retention (FLR-E & FLR-C) <p>Unified Protocols:</p> <ul style="list-style-type: none"> • File • Block • VVols <p>Local Protection:</p> <ul style="list-style-type: none"> • Controller Based Encryption (optional), with self-managed or external key management • Local Point-In-Time Copies (Snapshots and Thin Clones) • AppSync Basic • Dell EMC Common Event Enabler; AntiVirus Agent, Event Publishing Agent <p>Remote Protection:</p> <ul style="list-style-type: none"> • Native Asynchronous Block & File Replication • Native Synchronous Block & File Replication • MetroSync Manager (optional software to automate synchronous file replication sessions) • Snapshot Shipping • Dell EMC RecoverPoint Basic <p>Migration:</p> <ul style="list-style-type: none"> • Native Block & File migration from Dell EMC VNX • SAN Copy Pull: Integrated Block migration from 3rd party arrays <p>Performance Optimization for Hybrid Arrays:</p> <ul style="list-style-type: none"> • FAST Cache • FAST VP |
| Interface Protocols | NFSv3, NFSv4, NFSv4.1; CIFS (SMB 1), SMB 2, SMB 3.0, SMB 3.02, and SMB 3.1.1; FTP and SFTP; FC, iSCSI and VMware Virtual Volumes (VVols) 2.0 |
| Optional Software | <ul style="list-style-type: none"> • AppSync Advanced • Data Protection Suite: Backup, Archive and Collaboration Software • Dell EMC RecoverPoint Advanced • Dell EMC RP4VM • PowerPath Migration Enabler • PowerPath Multipathing • VPLEX |
| <p>Note: For more details on software licensing, please contact your sales representative</p> | |

Virtualization Solutions

Dell EMC Unity offers support for a wide variety of protocol and advanced features available via various software suites and packs including but not limited to:

- Dell EMC Storage Integrator (ESI): For provisioning within the Microsoft management context (Systems Center) for Hyper-V and SharePoint
- OpenStack Cinder Driver: For provisioning and managing block volumes within an OpenStack environment
- OpenStack Manila Driver: For managing shared file systems within an OpenStack environment
- Dell EMC Virtual Storage Integrator (VSI) for VMware vSphere™: For provisioning, management, and cloning
- VMware Site Recovery Manager (SRM) Integration: Managing failover and failback making disaster recovery rapid and reliable
- Virtualization API Integration: VMware: VAAI and VASA. Hyper-V: Offloaded Data Transfer (ODX) and Offload Copy for File

Electrical Specifications

All power figures shown represent a worst case product configuration with max normal values operating in an ambient temperature environment of 20°C to 25°C.

The chassis power numbers provided may increase when operating in a higher ambient temperature environment.

| Disk Processor Enclosure (DPE) | | | | |
|--|---|---|---|---|
| | 380F/380 DPE 25 2.5" SFF drives and four IO modules | 480F/480 DPE 25 2.5" SFF drives and four IO modules | 680F/680 DPE 25 2.5" SFF drives and four IO modules | 880F/880 DPE 25 2.5" SFF drives and four IO modules |
| POWER | | | | |
| AC Line Voltage | 100 to 240 VAC ± 10%, single phase, 47 to 63 Hz | | | |
| AC Line Current (operating maximum) | 10.07 A max at 100 VAC; 5.04 A max at 200VAC | 10.6 A max at 100 VAC; 5.3 A max at 200VAC | 11.72 A max at 100 VAC; 5.86 A max at 200VAC | 14.41 A max at 100 VAC; 7.2 A max at 200VAC |
| Power Consumption (operating maximum) | 1007 VA (970.5 W) max at 100 VAC; 1007 VA (970.5 W) max at 200 VAC | 1060 VA (1050 W) max at 100 VAC; 1060 VA (1050 W) max at 200 VAC | 1172 VA (1161 W) max at 100 VAC; 1172 VA (1161 W) max at 200 VAC | 1440.77 VA (1411.96 W) max at 100 VAC; 1440.77 VA (1411.96 W) max at 200 VAC |
| Power Factor | 0.95 minimum at full load, @ 100/ 200 VAC | | | |
| Heat Dissipation (operating maximum) | 3.49 x 10 ⁶ J/hr, (3,311 Btu/hr) max at 100 VAC; 3.49 x 10 ⁶ J/hr, (3,311 Btu/hr) max (100V) | 3.78 x 10 ⁶ J/hr, (3,581 Btu/hr) max at 100 VAC; 3.78 x 10 ⁶ J/hr, (3,581 Btu/hr) max 200VAC | 4.18 x 10 ⁶ J/hr, (3,960 Btu/hr) max at 100 VAC; 4.18 x 10 ⁶ J/hr, (3,960 Btu/hr) max 200VAC | 5.08 x 10 ⁶ J/hr, (4,818 Btu/hr) max at 100 VAC; 5.08 x 10 ⁶ J/hr, (4,818 Btu/hr) max 200VAC |
| In-rush Current | 45 Apk "cold" per line cord, at any line voltage | | | |
| Startup Surge Current | 120 Apk "hot" per line cord, at any line voltage | | | |
| AC Protection | 15 A fuse on each power supply, single line | 20 A fuse on each power supply, single line | | |
| AC Inlet Type (High Line) | IEC320-C14 appliance coupler, per power zone | | | |
| AC Inlet Type (Low Line) | IEC320-C20 appliance coupler, per power zone | | | IEC320-C14 appliance coupler, per power zone* |
| Ride-through Time | 10 ms min | | | |
| Current Sharing | ± 5 percent of full load, between power supplies | | | |
| * Requires customer supplied step-up transformer | | | | |

| DIMENSIONS | | | | |
|--|-------------------|-------------------|-------------------|-------------------|
| Weight kgs/lbs | empty 24.60/54.11 | empty 25.90/57.10 | empty 25.90/57.10 | empty 25.90/57.10 |
| Vertical size | 2 NEMA units | 2 NEMA units | 2 NEMA units | 2 NEMA units |
| Height cm/inches | 8.88/3.5 | 8.72/3.43 | 8.72/3.43 | 8.72/3.43 |
| Width cm/inches | 44.76/17.62 | 44.72/17.61 | 44.72/17.61 | 44.72/17.61 |
| Depth cm/inches | 61.39/24.17 | 79.55/31.32 | 79.55/31.32 | 79.55/31.32 |
| Note: Power consumption values for DPEs and DAEs are based on fully populated enclosures (power supplies, drives and I/O modules). | | | | |

| Disk Array Enclosure (DAE) | | | |
|--|--|--|--|
| | 25 X 2.5" Drive DAE | 80 X 2.5" Drive DAE | 15 X 3.5" Drive DAE |
| POWER | | | |
| AC Line Voltage | 100 to 240 VAC ± 10%, single phase, 47 to 63 Hz | | |
| AC Line Current (operating maximum) | 4.50 A max at 100 VAC, 2.40 A max at 200 VAC | 13.18 A max at 100 VAC, 6.59 A max at 200 VAC | 2.90 A max at 100 VAC, 1.60 A max at 200 VAC |
| Power Consumption (operating maximum) | 453.0 VA/ 432.0 W max at 100 VAC 485.0 VA/ 427.0 W max at 200VAC | 1318.0 VA/ 1233.0 W max at 100 VAC 1318.0 VA/ 1233.0 W max at 200VAC | 287.0 VA/ 281.0 W max at 100 VAC 313.0 VA/ 277.0 W max at 200VAC |
| Power Factor | 0.95 minimum at full load, @ 100V/200V | | 0.90 minimum at full load, @ 100V/200V |
| Heat Dissipation (operating maximum) | 1.56 x 10 ⁶ J/hr, (1,474 Btu/hr) max at 100 VAC 1.54 x 10 ⁶ J/hr, (1,457 Btu/hr) max at 200 VAC | 4.43 x 10 ⁶ J/hr, (4,207 Btu/hr) max at 100 VAC 4.43 x 10 ⁶ J/hr, (4,207 Btu/hr) max at 200 VAC | 1.01 x 10 ⁶ J/hr, (959 Btu/hr) max at 100 VAC 1.00 x 10 ⁶ J/hr, (945 Btu/hr) max at 200 VAC |
| In-rush Current | 30 Apk "cold" per line cord, at any line voltage | 45 Apk "cold" per line cord, at any line voltage | 30 A max "cold" for ½ line cycle, per line cord at 240 VAC |
| Startup Surge Current | 40 Apk "cold" per line cord, at any line voltage | 120 Apk "hot" per line cord, at any line voltage | 25 Amps peak max per line cord, at any line voltage |
| AC Protection | 15 A fuse on each power supply, single line | | 10 A fuse on each power supply, single line |
| AC Inlet Type | IEC320-C14 appliance coupler, per power zone | | |
| Ride-through Time | 12 ms minimum | 10 ms minimum | 30 ms minimum |
| Current Sharing | ± 5 percent of full load, between power supplies | | Droop Load Sharing |
| WEIGHT AND DIMENSIONS | | | |
| Weight kg/lbs | Empty: 10.0/22.1 Full: 20.23/44.61 | Empty: 11.33/25 Full: 58.9/130 | Empty: 14.5/32 Full: 30.8/68 |
| Vertical size | 2 NEMA units | 3 NEMA units | 3 NEMA units |
| Height cm/inches | 8.46/3.40 | 13.21/5.20 | 13.33/5.25 |
| Width cm/inches | 44.45/17.5 | 44.70/17.6 | 44.45/17.5 |
| Depth cm/inches | 33.02/13 | 76.20/30 | 35.56/14 |
| Note: Power consumption values for DPEs and DAEs are based on fully populated enclosures (power supplies, drives and I/O modules). | | | |

| Cabinets | |
|------------------------|---|
| | Standard 40U Cabinet |
| AC Line Voltage | 200 to 240 VAC ± 10%, single-phase, 47 to 63 Hz |
| Power Configuration | One, two, three or four power domains, each redundant |
| Power Inlet Count | Two, four, six, or eight (two per domain) |
| Plug Types | NEMA L6-30P or IEC309-332 P6 or IP57 (Australia) |
| Input Power Capacity | 1 Domain: 4,800 VA @ 200 VAC, 5,760 VA @ 240 VAC 2 Domain: 9,600 VA @ 200 VAC, 11,520 VA @ 240 VAC 3 Domain: 14,400 VA @ 200 VAC, 17,280 VA @ 240 VAC 4 Domain: 19,200 VA @ 200 VAC, 20,040 VA @ 240 VAC |
| AC Protection | 30 A site circuit breakers on each power branch |
| 40U Cabinet Dimensions | Height - 75 in (190.8 cm); Width - 24.0 in (61.1 cm); Depth - 39.0 in (99.2 cm); Weight Empty – 380 lb (173 kg) |

Operating environment

The Dell EMC Unity XT 480F/480 – 880F/880 models meet ASHRAE Equipment Class A3 and the 380F/380 models meet ASHRAE Equipment Class A4.

| | Description | Specification |
|--|--|--|
| Recommended Range Operation | The limits under which equipment will operate the most reliably while still achieving reasonably energy-efficient data center operation. | 18°C to 27°C (64.4°F to 80.6°F) at 5.5°C (59°F) dew. |
| Continuous Allowable Range Operation | Data center economization techniques (e.g. free cooling) may be employed to improve overall data center efficiency. These techniques may cause equipment inlet conditions to fall outside the recommended range but still within the continuously allowable range. Equipment may be operated without any hourly limitations in this range. | 5°C to 35°C (50°F to 95°F) at 20% to 80% relative humidity with 21°C (69.8°F) maximum dew point (maximum wet bulb temperature). De-rate maximum allowable dry bulb temperature at 1°C per 300m above 950m (1°F per 547 ft above 3117 ft). |
| Improbable Operation (Excursion Limited) | During certain times of the day or year, equipment inlet conditions may fall outside the continuously allowable range but still within the expanded improbable range. Equipment operation is limited to ≤ 10% of annual operating hours in this range. | 35°C to 40°C (with no direct sunlight on the equipment) at -12°C dew point and 8% to 85% relative humidity with 24°C dew point (maximum wet bulb temperature). Outside the continuously allowable range (10°C to 35°C), the system can operate down to 5°C or up to 40°C for a maximum of 10% of its annual operating hours. For temperatures between 35°C and 40°C (95°F to 104°F), de-rate maximum allowable dry bulb temperature by 1°C per 175m above 950m (1°F per 319 ft above 3117 ft). |
| Exceptional Operation (Excursion Limited) ASHRAE 4 only | During certain times of the day or year, equipment inlet conditions may fall outside the continuously allowable range but still within the expanded exceptional range. Equipment operation is limited to ≤ 1% of annual operating hours in this range. | 40°C to 45°C (with no direct sunlight on the equipment) at -12°C dew point and 8% to 90% relative humidity with 24°C dew point (maximum wet bulb temperature). Outside the continuously allowable range (10°C to 35°C), the system can operate down to 5°C or up to 45°C for a maximum of 1% of its annual operating hours. For temperatures between 35°C and 45°C (95°F to 104°F), de-rate maximum allowable dry bulb temperature by 1°C per 125m above 950m (1°F per 228 ft above 3117 ft). |
| Temperature Gradient | | 20°C / hour (36°F / hour) |
| Altitude | Max Operating | 3050m (10,000ft) |

Statement of Compliance

This Information Technology Equipment is compliant with the electromagnetic compatibility (Dell EMC) and product safety regulations/standards required by the countries in which the product is sold. Dell EMC compliance is based on FCC part 15, CISPR 32/CISPR24 and EN55032/EN55024 standards, including applicable international variations. Dell EMC compliant Class A products are marketed for use in business, industrial, and commercial environments. Product Safety compliance is based on IEC/EN 60950-1 and IEC/EN 62368-1 standards, including applicable national deviations.

This Information Technology Equipment is in compliance with EU RoHS Directive 2011/65/EU.

The individual devices used in this product are approved under a unique regulatory model identifier that is affixed to each individual device rating label, which may differ from any marketing or product family name in this data sheet.

For additional information see <https://support.emc.com>, under the Safety & EMI Compliance Information tab.

Dell EMC, the Dell EMC logo, AppSync, CloudIQ, Data Protection Suite, EMC2, Dell EMC Unity, Unisphere, Dell EMC RecoverPoint, PowerPath, and VPLEX are registered trademarks or trademarks of Dell EMC in the United States and other countries. VMware, vCenter, vSphere, and the VMware logo are registered trademarks or trademarks of VMware, Inc., in the United States and other jurisdictions.

Dell EMC believes the information in this document is accurate as of its publication date. The information is subject to change without notice.



[Learn more](#) about Dell EMC Unity solutions



[Contact](#) a Dell EMC Expert